

Name _____ Date _____ Truck / City _____ Event _____

Front Suspension

Upper Spacer: _____ mm

4.8mm Ball Stud: Camber: _____ °

UM128 (Std) UMW508 (+2mm High Mount)

4.8mm Ball Stud Spacer: _____ mm

Axle Spacer: Out _____ mm In _____ mm

4.8mm Ball Stud: LA246 (-1mm Low Mount) UM129 (Std)

Ackerman Steer Spacer: _____ mm

Wheel Hub: _____ mm

Bump Steer Spacer: _____ mm

Axle Height Spacer: _____ mm _____ mm

Toe: In Out _____ °

Caster: 25° 30°

Spacer: 0.5 1.0 None

Caster Block: 0° 2° 4°

Block position: IN OUT

Front Bulkhead Weight Placement:

None

Bulkhead Inside _____ oz _____ g

On the skid plate _____ oz _____ g * 1oz=28g

Wheelbase: F: _____ mm R: _____ mm

Comments: _____

Rear Suspension

Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Anti-Squat: _____ °

4.8mm Ball Stud: UM129 (Std) UMW508 (+2mm High Mount) 97050M

Sway Bar: None _____ mm

Camber: _____ °

Upper Spacer: _____ mm

Wheelbase: F: _____ mm R: _____ mm

RR: _____ mm

Mid: _____ mm

Lower Sus Holder: Normal RF Aluminum(Opt) UMW511+UMW512 UMW514+UMW515

Wide: RF2

Wheelbase: F: _____ mm R: _____ mm

Rear Hub add Toe: 0°Type-B (UM519) 0°Type-B2 (UM519-2) 0°Alu (UMW516-0) 0.5°Alu (UMW516-05) 1°Alu (UMW516-1)

Axle Spacer: Out _____ mm In _____ mm

Motor Position: Rear Motor Midship Motor

Diff: Gear Diff. # _____ Ball Diff.

Comments: _____

Shock

| | Front | Rear |
|------------------|---|--|
| Shock Piston: | _____ | _____ |
| Shock Oil: | # _____ | # _____ |
| Shock Spring: | _____ | _____ |
| Limiters: | in _____ mm out _____ mm | in _____ mm out _____ mm |
| Shock Length(A): | _____ mm | _____ mm |
| Shock Length(B): | _____ mm | _____ mm |
| Shock Length(C): | _____ mm | _____ mm |
| Ball End type: | Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L | Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L |

Chassis

Screw: _____

Ride Height: F _____ mm R _____ mm

Battery Position

Battery Type: Straight Separate Short

Battery Placement: Front Rear

Tire

| | Front | Rear |
|--------------------|-------|-------|
| Tire: | _____ | _____ |
| Inserts: | _____ | _____ |
| Wheel: | _____ | _____ |
| Traction Compound: | _____ | _____ |

Electronics

Motor: _____

Pinion/Spur: _____

Battery: _____

ESC: _____

Truck Condition

Smooth Sandy Bumpy Soft Dirt Low Truction Grass Med. Truction Blue Groove Higt Truction Clay Wet Dusty Dry Other

Wing

Blast-S Wing Mount : Blast-L Narrow Step-S Wide Step-M Wing Angle : Step-L 4° Step 2.0 7° 10°

Lip : _____

Comment
