

Name _____ Date _____ Truck / City _____ Event _____

Front Suspension

Upper Spacer: _____ mm

4.8mm Ball Stud: Camber: _____ °

UM128 (Std)

UMW508 (+2mm High Mount)

4.8mm Ball Stud:

LA246 (-1mm Low Mount)

UM129 (Std)

Ackerman Steer Spacer: _____ mm

Axle Spacer:

Out _____ mm

In _____ mm

Wheel Hub: _____ mm

Bump Steer Spacer: _____ mm

Axle Height Spacer:

_____ mm

_____ mm

Toe: In Out _____ °

Caster:

25°

30°

Spacer:

0.5

1.0

None

Caster Block:

0°

2°

4°

Block position:

IN

OUT

Front Bulkhead Weight Placement:

None

Bulkhead Inside _____ oz _____ g

On the skid plate _____ oz _____ g * 1oz=28g

Wheelbase: F: _____ mm R: _____ mm

Comments: _____

Rear Suspension

Sus Holder Spacer:

F 0.5 1.0 None

R 0.5 1.0 None

Anti-Squat: _____ °

Sway Bar: None _____ mm

Upper Spacer: _____ mm

4.8mm Ball Stud:

UM129 (Std)

UMW508 (+2mm High Mount)

97050M

Camber: _____ °

Wheelbase: F: _____ mm R: _____ mm

RR: _____ mm

Mid: _____ mm

Lower Sus Holder:

Normal RF Aluminum(Opt) UMW511+UMW512

Narrow RF2 UMW514+UMW515

Wide RF2 UMW514+UMW515

Upper Spacer: _____ mm

Wheelbase: F: _____ mm R: _____ mm

Rear Hub add Toe:

0°Type-B (UM519)

0°Type-B2 (UM519-2)

0°Alu (UMW516-0)

0.5°Alu (UMW516-05)

1°Alu (UMW516-1)

Axle Spacer:

Out _____ mm

In _____ mm

Comments: _____

Motor Position

- Rear Motor
- Midship Motor

Diff.

- Gear Diff. # _____
- Ball Diff.

Shock

	Front		Rear	
Shock Piston:	_____	_____	_____	_____
Shock Oil:	# _____	# _____	# _____	# _____
Shock Spring:	_____	_____	_____	_____
Limiters:	in _____ mm	out _____ mm	in _____ mm	out _____ mm
Shock Length(A):	_____ mm	_____ mm	_____ mm	_____ mm
Shock Length(B):	_____ mm	_____ mm	_____ mm	_____ mm
Shock Length(C):	_____ mm	_____ mm	_____ mm	_____ mm
Ball End type:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L		Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	

Chassis

Screw:

Ride Height: F _____ mm R _____ mm

Battery Position

- Battery Type:**
- Straight
- Separate
- Short
- Battery Placement:**
- Front
- Rear

Tire

	Front	Rear
Tire:	_____	_____
Inserts:	_____	_____
Wheel:	_____	_____
Traction Compound:	_____	_____

Electronics

Motor: _____

Pinion/Spur: _____

Battery: _____

ESC: _____

Truck Condition

- Smooth
- Bumpy
- Low Truction
- Med. Truction
- Higt Truction
- Wet
- Dry
- Sandy
- Soft Dirt
- Grass
- Blue Groore
- Clay
- Dusty
- Other

Wing

- Blast-S
- Blast-L
- Step-S
- Step-M
- Step-L
- Step 2.0
- Lip: _____
- Wing Mount:**
- Narrow
- Wide
- Wing Angle:**
- 4°
- 7°
- 10°

Comment
