

Name _____ Date _____ Track / City _____ Event _____

Front Suspension

Upper Spacer: _____ mm

Front Tower:
☐ Std
☐ Carbon

Toe: ☐ In ☐ Out _____°

Tie Rod: _____

Front Bulkhead Weight Placement:
☐ None
☐ Bulkhead Inside _____ oz _____ g
☐ On the skid plate _____ oz _____ g

4.8mm Ball Stud:
☐ UM128 (Std)
☐ UMW508 (+2mm High Mount)

4.8mm Ball Stud Spacer: _____ mm

Caster:
☐ 25° ☐ 30° ☐ 0.5 ☐ 1.0 ☐ None ☐ 0° ☐ 2° ☐ 4°

Spacer:
☐ A (UM502)
☐ B (UM721/Std)
☐ C (UM567)

Front Axle: ☐ UM569 (RB6) ☐ UM506 (RB5)

Front Arm: ☐ Std ☐ Carbon

Camber: _____°

Axle Spacer:
☐ Out _____ mm
☐ In _____ mm

Wheel Hub: _____ mm

Caster Block position:
☐ IN (wide/Std)
☐ OUT (Narrow)

4.8mm Ball Stud:
☐ LA246 (-1mm Low Mount)
☐ 97050M (Std)

Ackerman Steer Spacer: _____ mm

C-Hub: ☐ Std ☐ Carbon

Knuckle: ☐ Std ☐ Carbon

Bump Steer Spacer: _____ mm

Axle Height Spacer:
☐ _____ mm
☐ _____ mm

Wheelbase: F: _____ mm R: _____ mm

Comments: _____

Rear Suspension

Rear Tower:
☐ Std
☐ Carbon

RR: _____

Mid: _____

Sus Holder Spacer:
 F ☐ 0.5 ☐ 1.0 ☐ None
 R ☐ 0.5 ☐ 1.0 ☐ None

Anti-Squat: _____°

4.8mm Ball Stud:
☐ UM129
☐ UMW508 (+2mm High Mount)
☐ 97050M
☐ UM128 (Std)

Sway Bar: ☐ None ☐ _____ mm

Universal Swing Shaft: _____

Upper Spacer: _____ mm

Lower Sus Holder:
 Normal Aluminum(Opt)
 Narrow ☐ RF ☐ UMW511+UMW512 ☐ RM UMW705+UMW706
 Wide ☐ RF2 ☐ UMW514+UMW515 ☐ MM UMW705+UMW707

Upper Spacer: _____ mm

Hub Spacing:
 F: _____ mm
 R: _____ mm

Outer Bearing:
☐ 5x10
☐ 5x11
☐ 5x13

Wheelbase (arm): F: _____ mm R: _____ mm

Camber: _____°

Axle Spacer:
☐ Out _____ mm
☐ In _____ mm

Rear Arm:
☐ UM713
☐ UM521/566
☐ UM521-1
☐ UM503 (Short)
☐ UM711 (Carbon)

Rear Hub Toe:
☐ UM519
☐ UM519-2
☐ 0° Alu (UMW704-0)
☐ 0.5° Alu (UMW704-05)
☐ 1° Alu (UMW704-1)

Comments: _____

Motor Position

☐ Rear Motor
☐ Midship Motor

Diff.

☐ Gear Diff. # _____
☐ Ball Diff.

Shock

Front **Rear**

Shock Piston: _____

Shock Oil: # _____ # _____

Shock Spring: _____

Limiters: in _____ mm out _____ mm

Shock Length(A): _____ mm

Shock Length(B): _____ mm

O-ring: _____

Ball End type: Front: ☐ S ☐ M ☐ L
 Rear: ☐ S ☐ M ☐ L

Shock Cap: ☐ UM719 (Std) ☐ UM753-1 (Bleeder)

Battery Placement:

☐ UM787 ☐ None ☒ Screw

Comment: _____

Front **Rear**

Foam:
☐ Front
☐ Rear
☐ None

Chassis

☐ Kit ☐ UMW720 (LW)

F _____ mm **Ride Height** **R** _____ mm

Battery Type

☐ Straight
☐ Separate
☐ Short
☐ Sideways

Type: _____

Other

Motor: _____
ESC: _____
Pinion/Spur: _____

Tire

Tire **Compound** **Insert** **Wheel**

Front: _____
Rear: _____
Comment: _____

Comments

Track Condition

☐ Smooth
☐ Bumpy
☐ Low Traction
☐ Med. Traction
☐ High Traction
☐ Wet
☐ Dry

Aero

☐ Blast-S
☐ Blast-L
☐ Step-S
☐ Step-M
☐ Step-L
☐ Step 2.0
☐ Lip : _____

Body:

Wing Mount:
☐ Narrow
☐ Wide
Wing Angle:
☐ 4°
☐ 7°
☐ 10°