

Name _____ Date _____ Truck / City _____ Event _____

Front Suspension

Upper Spacer: _____ mm

4.8mm Ball Stud: Camber: _____ °

UM128 (Std) UMW508 (+2mm High Mount)

4.8mm Ball Stud Spacer: _____ mm

Axle Spacer: Out _____ mm In _____ mm

4.8mm Ball Stud: LA246 (-1mm Low Mount) UM129 (Std)

Ackerman Steer Spacer: _____ mm

Wheel Hub: _____ mm

Bump Steer Spacer: _____ mm

Toe: In Out _____ °

Caster: 25° 30°

Spacer: 0.5 1.0 None

Caster Block: 0° 2° 4°

Block position: IN OUT

Axle Height Spacer: _____ mm _____ mm

Front Bulkhead Weight Placement: None Bulkhead Inside _____ oz _____ g On the skid plate _____ oz _____ g * 1oz=28g

Comments: _____

Wheelbase: F: _____ mm R: _____ mm

Rear Suspension

Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Anti-Squat: _____ °

Upper Spacer: _____ mm

4.8mm Ball Stud: UM129 (Std) UMW508 (+2mm High Mount) 97050M

Sway Bar: None _____ mm

Camber: _____ °

Wheelbase: F: _____ mm R: _____ mm

RR: _____

Mid: _____

Lower Sus Holder: Normal RF Aluminum(Opt) UMW511+UMW512 Wide RF2 UMW514+UMW515

Upper Spacer: _____ mm

Axle Spacer: Out _____ mm In _____ mm

Wheelbase: F: _____ mm R: _____ mm

Rear Hub add Toe: 0°Type-B (UM519) 0°Type-B2 (UM519-2) 0°Alu (UMW516-0) 0.5°Alu (UMW516-05) 1°Alu (UMW516-1)

Comments: _____

Motor Position

Rear Motor Midship Motor

Diff.

Gear Diff. # _____ Ball Diff.

Shock

	Front	Rear
Shock Piston:	_____	_____
Shock Oil:	# _____	# _____
Shock Spring:	_____	_____
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	_____ mm	_____ mm
Shock Length(B):	_____ mm	_____ mm
Shock Length(C):	_____ mm	_____ mm
Ball End type:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	

Chassis

Screw: _____

Ride Height: F _____ mm R _____ mm

Battery Position

Battery Type: Straight Separate Short

Battery Placement: Front Rear

Tire

	Front	Rear
Tire:	_____	_____
Inserts:	_____	_____
Wheel:	_____	_____
Traction Compound:	_____	_____

Electronics

Motor: _____

Pinion/Spur: _____

Battery: _____

ESC: _____

Truck Condition

Smooth Sandy Bumpy Soft Dirt Low Truction Grass Med. Truction Blue Groove Higt Truction Clay Wet Dusty Dry Other

Wing

Wing Mount: Blast-S Blast-L Step-S Step-M Step-L Step 2.0 Lip: _____

Wing Angle: Narrow Wide 4° 7° 10°

Comment
