

Name \_\_\_\_\_ Date \_\_\_\_\_ Truck / City \_\_\_\_\_ Event \_\_\_\_\_

### Front Suspension

Upper Spacer: \_\_\_\_\_ mm

4.8mm Ball Stud: Camber: \_\_\_\_\_ °

UM128 (Std)  UMW508 (+2mm High Mount)

4.8mm Ball Stud Spacer: \_\_\_\_\_ mm

Axle Spacer:  Out \_\_\_\_\_ mm  In \_\_\_\_\_ mm

Wheel Hub: \_\_\_\_\_ mm

4.8mm Ball Stud:  LA246 (-1mm Low Mount)  UM129 (Std)

Ackerman Steer Spacer: \_\_\_\_\_ mm

Bump Steer Spacer: \_\_\_\_\_ mm

Toe:  In  Out \_\_\_\_\_ °

Caster:  25°  30°

Spacer:  0.5  1.0  None

Caster Block:  0°  2°  4°

Block position:  IN  OUT

Axle Height Spacer:  \_\_\_\_\_ mm  \_\_\_\_\_ mm

Front Bulkhead Weight Placement:  None  Bulkhead Inside \_\_\_\_\_ oz \_\_\_\_\_ g  On the skid plate \_\_\_\_\_ oz \_\_\_\_\_ g \* 1oz=28g

Comments: \_\_\_\_\_

Wheelbase: F: \_\_\_\_\_ mm R: \_\_\_\_\_ mm

### Rear Suspension

Sus Holder Spacer: F  0.5  1.0  None R  0.5  1.0  None

Anti-Squat: \_\_\_\_\_ °

Upper Spacer: \_\_\_\_\_ mm

4.8mm Ball Stud:  UM129 (Std)  UMW508 (+2mm High Mount)  97050M

Sway Bar:  None  \_\_\_\_\_ mm

Camber: \_\_\_\_\_ °

Wheelbase: F: \_\_\_\_\_ mm R: \_\_\_\_\_ mm

RR: \_\_\_\_\_

Mid: \_\_\_\_\_

Lower Sus Holder: Normal  RF  Aluminum(Opt)  UMW511+UMW512  Wide  RF2  UMW514+UMW515

Upper Spacer: \_\_\_\_\_ mm

Wheelbase: F: \_\_\_\_\_ mm R: \_\_\_\_\_ mm

Rear Hub add Toe:  0°Type-B (UM519)  0°Type-B2 (UM519-2)  0°Alu (UMW516-0)  0.5°Alu (UMW516-05)  1°Alu (UMW516-1)

Axle Spacer:  Out \_\_\_\_\_ mm  In \_\_\_\_\_ mm

Comments: \_\_\_\_\_

### Motor Position

- Rear Motor  Midship Motor

### Diff.

- Gear Diff. # \_\_\_\_\_  Ball Diff.

### Shock

	Front	Rear
Shock Piston:	_____	_____
Shock Oil:	# _____	# _____
Shock Spring:	_____	_____
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	_____ mm	_____ mm
Shock Length(B):	_____ mm	_____ mm
Shock Length(C):	_____ mm	_____ mm
Ball End type:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L

### Chassis

Screw: \_\_\_\_\_

Ride Height: F \_\_\_\_\_ mm R \_\_\_\_\_ mm

### Battery Position

- Battery Type:  Straight  Separate  Short
- Battery Placement:  Front  Rear

### Tire

	Front	Rear
Tire:	_____	_____
Inserts:	_____	_____
Wheel:	_____	_____
Traction Compound:	_____	_____

### Electronics

Motor: \_\_\_\_\_

Pinion/Spur: \_\_\_\_\_

Battery: \_\_\_\_\_

ESC: \_\_\_\_\_

### Truck Condition

- Smooth  Sandy  Bumpy  Soft Dirt  Low Truction  Grass  Med. Truction  Blue Groove  Higt Truction  Clay  Wet  Dusty  Dry  Other

### Wing

- Blast-S  Wing Mount :  Blast-L  Narrow  Step-S  Wide  Step-M  Wing Angle :  Step-L  4°  Step 2.0  7°  10°
- Lip: \_\_\_\_\_

### Comment

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_