

ULTIMA RB6.6 SET UP SHEET

KYOSHO
THE FINEST RADIO CONTROL MODELS

Name _____

Date _____

Truck / City _____

Event _____

Front Suspension

Upper Spacer: _____ mm

4.8mm Ball Stud: **Camber:** _____
☐ UM128(Std.)
☐ UMW508 (+2mm High Mount)

4.8mm Ball Stud Spacer: _____ mm

AL. Steering Support:
☐ None
☐ UMW724

Axle Spacer:
☐ Out _____ mm
☐ In _____ mm

Wheel Hub:
☐ UM569 / Std
☐ UM506

4.8mm Ball Stud:
☐ LA246 (-1mm Low Mount)
☐ 97050M (Std)

Ackerman Steer Spacer: _____ mm
☐ UMW701 Aluminum ST Plate
☐ UMW702 Aluminum Clank Arm

Toe: ☐ In ☐ Out _____°

Tie Rod: _____

Front Bulkhead Weight Placement:
☐ None
☐ Bulkhead Inside _____ oz _____ g
☐ On the skid plate _____ oz _____ g * 1oz=28g

Caster:
☐ 25°
☐ 30°

Caster Block:
☐ 0.5 ☐ 0°
☐ 1.0 ☐ 2°
☐ None ☐ 4°

Caster Block Position:
☐ IN (wide/Std)
☐ OUT (Narrow)

Spacer:
☐ A (UM502) ☐ B(UMW722/Brass)
☐ B (UM721/Std) ☐ B(UMW723/Alu)
☐ C (UM567)

Bump Steer Spacer: _____ mm

Axle Height Spacer:
☐ _____ mm
☐ _____ mm

Wheelbase: F: _____ mm R: _____ mm

Comments: _____

Rear Suspension

Sus Holder Spacer:
 F ☐ 0.5 ☐ 1.0 ☐ None
 R ☐ 0.5 ☐ 1.0 ☐ None

Anti-Squat: _____°

4.8mm Ball Stud:
☐ UM129
☐ UMW508 (+2mm High Mount)
☐ 97050M
☐ UM128(Std.)

Upper Spacer: _____ mm

Wheelbase:
 F: _____ mm
 R: _____ mm

Universal Swing Shaft: _____

Camber: _____°

Drive Hub :
☐ 4mm (TFW113)
☐ 4.5mm (LAW30GM/Std.)
☐ 5.2mm (UMW523)

Axle Spacer:
☐ Out _____ mm
☐ In _____ mm

Lower Sus. Holder:
 Plastic
☐ RF ☐ RF2L
☐ RF2
 Option
☐ UMW511GM (RF/Alu)

Diff.
☐ Gear Diff. # _____
☐ Ball Diff.

Rear Hub Carrier :
☐ 0°Type-B (UM519)
☐ 0°Type-B2 (UM519-2)
☐ 0° Alu (UMW704-0)
☐ 0.5°Alu (UMW704-05)
☐ 1°Alu (UMW704-1)

RR: _____

Mid: _____

Upper Spacer: _____ mm

Wheelbase:
 F: _____ mm
 R: _____ mm

Sway Bar: ☐ None ☐ _____ mm

Shock

Front **Rear**

Shock Piston: _____

Shock Oil: # _____ # _____

Shock Spring: _____

Limiters: in out mm in out mm

Shock Length(A): _____ mm _____ mm

O-ring: _____

Shock Top type: ☐ Alu(UM719/Std) ☐ UM753-1

Ball End type: Front: ☐ S ☐ M ☐ L
 Rear: ☐ S ☐ M ☐ L

Battery Placement:

☐ None ☐ Screw

Front **Rear**

Foam:
☐ Front
☐ Rear
☐ None

Transmission

☐ Rear Motor
☐ Mid-Ship 3 Gear
☐ Mid-Ship 4 Gear
☐ Mid-Ship Laydown

Chassis

F _____ mm **Ride Height:** **R** _____ mm

Battery Type

☐ Straight
☐ Separate
☐ Short

Truck Condition

☐ Smooth ☐ Sandy
☐ Bumpy ☐ Soft Dirt
☐ Low Truction ☐ Grass
☐ Med. Truction ☐ Blue Groove
☐ Higt Truction ☐ Clay
☐ Wet ☐ Dusty
☐ Dry ☐ Other

Wing

Wing Mount :
☐ Blast-S ☐ Narrow
☐ Blast-L ☐ Wide
☐ Step-S
☐ Step-M
☐ Step-L
☐ Step 2.0
☐ Step 3.0
☐ Straight
☐ Round

Wing Angle :
☐ 4°
☐ 7°
☐ 10°

Lip : _____

Tire

Front **Rear** **Traction Compound or comment:**

Tire: _____

Inserts: _____

Wheel: _____

Other

Motor: _____

ESC: _____

Pinion/Spur: _____

Comment
