

Name _____ Date _____ Track / City _____ Event _____

Front Suspension

Upper Spacer: _____ mm

Toe: ☐ In ☐ Out _____°

Tie Rod: _____

Front Bulkhead Weight Placement:

☐ None

☐ Bulkhead Inside _____ oz _____ g

☐ On the skid plate _____ oz _____ g * 1oz=28g

4.8mm Ball Stud: Camber:

☐ UM128(Std.)

☐ UMW508 (+2mm High Mount)

4.8mm Ball Stud Spacer: _____ mm

Caster:

☐ 25°

☐ 30°

Caster Block:

☐ 0.5 ☐ 0°

☐ 1.0 ☐ 2°

☐ None ☐ 4°

Caster Block Position:

☐ IN (wide/Std)

☐ OUT (Narrow)

Wheel Hub:

☐ UM569 / Std

☐ UM506

AL. Steering Support:

☐ None

☐ UMW724

4.8mm Ball Stud:

☐ LA246 (-1mm Low Mount)

☐ 97050M (Std)

Ackerman Steer Spacer: _____ mm

☐ UMW701 Aluminum ST Plate

☐ UMW702 Aluminum Clank Arm

Bump Steer Spacer: _____ mm

Axle Height Spacer:

☐ _____ mm

☐ _____ mm

Wheelbase: F: _____ mm R: _____ mm

Comments: _____

Rear Suspension

4.8mm Ball Stud:

☐ UM129

☐ UMW508 (+2mm High Mount)

☐ 97050M

☐ UM128(Std.)

Upper Spacer: _____ mm

RR:

Mid:

Lower Sus. Holder:

Plastic

☐ RF ☐ RF2L

☐ RF2

Option

☐ UMW511GM (RF/Alu)

Sus Holder Spacer:

F ☐ 0.5 ☐ 1.0 ☐ None

R ☐ 0.5 ☐ 1.0 ☐ None

Anti-Squat: _____°

Camber: _____°

Universal Swing Shaft:

Drive Hub :

☐ 4mm (TFW113)

☐ 4.5mm (LAW30GM/Std.)

☐ 5.2mm (UMW523)

Axle Spacer:

☐ Out _____ mm

☐ In _____ mm

Block:

☐ _____

☐ _____

☐ _____

☐ _____

Wheelbase:

F: _____ mm

R: _____ mm

Wheelbase:

F: _____ mm

R: _____ mm

Sway Bar: ☐ None ☐ _____ mm

Rear Hub Carrier :

☐ 0°Type-B (UM519)

☐ 0°Type-B2 (UM519-2)

☐ 0° Alu (UMW704-0)

☐ 0.5°Alu (UMW704-05)

☐ 1°Alu (UMW704-1)


Diff.

☐ Gear Diff. # _____

☐ Ball Diff.

Shock

	Front	Rear
Shock Piston:	_____	_____
Shock Oil:	# _____	# _____
Shock Spring:	_____	_____
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	_____ mm	_____ mm
O-ring:	_____	_____
Shock Top type:	☐ Alu(UM719/Std)	☐ UM753-1
Ball End type:	Front: ☐ S ☐ M ☐ L	Rear: ☐ S ☐ M ☐ L



Battery Placement:

☐ None ☐ Screw

Front **Rear**

Foam:

☐ Front

☐ Rear

☐ None

Transmission

☐ Rear Motor

☐ Mid-Ship 3 Gear

☐ Mid-Ship 4 Gear

☐ Mid-Ship Laydown

Chassis

F _____ mm **Ride Height:** R _____ mm

Battery Type

☐ Straight

☐ Separate

☐ Short

Type: _____

Track Condition

☐ Smooth ☐ Sandy

☐ Bumpy ☐ Soft Dirt

☐ Low Traction ☐ Grass

☐ Med. Traction ☐ Blue Groove

☐ High Traction ☐ Clay

☐ Wet ☐ Dusty

☐ Dry _____

Wing

Wing Mount :

☐ Blast-S ☐ Narrow

☐ Blast-L ☐ Wide

☐ Step-S

☐ Step-M

☐ Step-L

☐ Step 2.0

☐ Step 3.0

☐ Straight

☐ Round

Wing Angle :

☐ 4°

☐ 7°

☐ 10°

Lip : _____

Tire

	Front	Rear
Tire:	_____	_____
Inserts:	_____	_____
Wheel:	_____	_____

Other

Motor: _____

ESC: _____

Pinion/Spur: _____