

Name _____ Date _____ Track / City _____ Event _____

Front Suspension

Upper Spacer: _____ mm

Shock Tower: _____ mm

Toe: ☐ In ☐ Out _____°

Toe Rod: _____ mm

Front Bulkhead Weight Placement:

☐ None

☐ Bulkhead Inside _____ oz _____ g

☐ On the skid plate _____ oz _____ g (*1oz = 28g)

4.8mm Ball Stud:

☐ UM128 (Std)

☐ UMW508 (+2mm High Mount)

Caster:

☐ 25°

☐ 30°

Spacer:

☐ A (UM502)

☐ B (UMW722/Brass)

☐ B (UMW723/Alu)

☐ C (UM567)

Caster Block:

☐ 0.5

☐ 1.0

☐ None

☐ 0°

☐ 2°

☐ 4°

Comments: _____

AI Steering Support:

☐ None

☐ UMW724

4.8mm Ball Stud:

☐ LA246 (-1mm Low Mount)

☐ 97050M (STD)

Ackermann Steer Spacer:

_____ mm

☐ UMW701 Aluminum ST Plate

☐ UMW702 Aluminum Crank Arm

Wheel Hub:

☐ UM569/Std

☐ UM506

Caster Block Position:

☐ In (Wide/Std)

☐ Out (Narrow)

Bump Steer Spacer:

_____ mm

Axel Height Spacer:

☐ _____ mm

☐ _____ mm

Wheelbase: F _____ mm R _____ mm

Rear Suspension

Shock Position:

☐ Front ☐ Rear

Shock Tower:

RR:

Mid:

Susp Holder Spacer:

F ☐ 0.5 ☐ 1.0 ☐ None

R ☐ 0.5 ☐ 1.0 ☐ None

Anti-Squat: _____°

4.8mm Ball Stud:

☐ UM129

☐ UMW508 (+2mm High Mount)

☐ 97050M

☐ UM128 (Std)

Upper Spacer: _____ mm

Lower Susp Holder:

Plastic ☐ RF ☐ RF2L ☐ RF2

Option ☐ UMW511GM (RF/Alu)

(Opt/Adjustable)

☐ UMW705 (RF/Alu) _____ Block

☐ UMW725 (RF-MID/Bra) _____ Block

(Opt/Adjustable)

☐ UMW706 (RR-RWD) _____ Block

☐ UMW707 (RR-MID) _____ Block

Universal Swing Shaft:

Camber: _____°

Drive Hub:

☐ 4mm (TFW113)

☐ 4.5mm (LAW30GM/Std.)

☐ 5.2mm (UMW523)

Axle Spacer:

☐ Out _____ mm

☐ In _____ mm

Sway Bar: ☐ None ☐ _____ mm

Upper Spacer: _____ mm

Wheelbase: F _____ mm R _____ mm

Wheelbase: F _____ mm R _____ mm

Comments: _____

Shocks

Front Rear

Piston: _____

Oil: # _____ # _____

Spring: _____

Limiters: In _____ mm In _____ mm

Out _____ mm Out _____ mm


Length (A): _____ mm _____ mm

O-Ring: _____

Shock Top Type: ☐ Alu (UM719/Std) ☐ UM753-1

Ball End Type: Front ☐ S ☐ M ☐ L

Rear ☐ S ☐ M ☐ L



Battery placement

Front

Chassis

☐ Stock ☐ UM731

F _____ mm Ride Height R _____ mm

Transmission

☐ Rear Motor

☐ Mid-Ship 3 Gear

☐ Mid-Ship 4 Gear

☐ Mid-Ship Laydown

Battery Type

☐ Straight

☐ Separate

☐ Short

Type _____

Track Condition

☐ Smooth ☐ Sandy

☐ Bumpy ☐ Soft Dirt

☐ Low Traction ☐ Grass

☐ Med. Traction ☐ Blue Groove

☐ High Traction ☐ Clay

☐ Wet ☐ Dusty

☐ Dry _____

Wing

Wing Mount: ☐ Narrow ☐ Wide

Wing Angle: ☐ 4° ☐ 7° ☐ 10°

☐ Blast-S

☐ Blast-L

☐ Step-S

☐ Step-M

☐ Step-L

☐ Step 2.0

☐ Step 3.0

☐ Straight Lip: _____

☐ Round _____

Tire

Front Rear

Tire _____

Insert _____

Wheel _____

Other

Motor: _____

ESC: _____

Ratio: _____