


ULTIMA RZ6 SET UP SHEET

KYOSHO
THE FINEST RADIO CONTROL MODELS

Name _____ Date _____ Track / City _____ Event _____

Front Suspension:

Shock Position:



Toe: ☐ In ☐ Out _____°

Tie Rod: _____

Front Bulkhead

Weight Placement:

- ☐ None
☐ Bulkhead Inside _____ g
☐ On the skid plate _____ g

4.8mm Ball Stud:

- ☐ UM128(Std.)
☐ UMW508(+2mm High Mount)

Upper Spacer:



Caster:

- ☐ 25°
☐ 30°
☐ A (UM502)
☐ B (UM721/Std)
☐ B (UMW722/Brass)
☐ B (UMW723/Alu)
☐ C (UM567)

Spacer:

- ☐ 0.5
☐ 1.0
☐ None

Caster Block:

- ☐ 0°
☐ 2°
☐ 4°

Camber:

_____°
 - +

AL. Steering Support:

- ☐ None
☐ UMW724

4.8mm Ball Stud:

- ☐ LA246 (-1mm Low Mount)
☐ 97050M (Std)

Ackerman Steer Spacer:

_____ mm


Ackerman arrow direction:

- ☐ Front(std) ☐ Rear

Option:

- ☐ UMW701 Alu ST Plate
☐ UMW702 Alu Clank Arm

Bump Steer Spacer:



Axle Height Spacer:

_____ mm
 _____ mm

Wheelbase: F: _____ mm R: _____ mm

Comments: _____

Rear Suspension:

Shock Position:




Wing Stay Position:

Shock Stay Type:

- ☐ LA352(std)
☐ LAW59
 (Carbom/2mmLow)

Upper Arm Position:



Sus.Arm:

- ☐ LA272(std)
☐ UM713B

4.8mm Ball Stud:

- ☐ 97050M(Std)
☐ UM129

Upper Spacer:

_____ mm


Camber:

_____°
 - +

Upper Spacer:

_____ mm

Hub Carrier:



- ☐ 0°Type-B(UM519)
☐ 0°Type-B2(UM519-2)
☐ 0°Alu(UMW704-0)
☐ 0.5°Alu(UMW704-05)
☐ 1°Alu(UMW704-1)

Front: _____ mm Rear: _____ mm

Wheelbase:

_____ mm _____ mm _____ mm _____ mm

Lower Sus Holder Block:

Front _____ Rear _____

Lower Sus Holder Spacer:

Front _____ mm Rear _____ mm

Comments:

Shock:

Front

Rear

Shock Piston:

Shock Oil:

#

#

Shock Spring:

Limiters:

in

mm

in

mm

out

mm

out

mm

Shock Length(A):

_____ mm

_____ mm

Shock Too Type:

- ☐ Alu(UM719/Std)

- ☐ UM753-1

5.8mm Ball End:

Front:



☐ S



☐ M



☐ L

Rear:



☐ S



☐ M



☐ L

Body / Wing:

Body:

Wing Mount:

- ☐ Narrow ☐ Wide

Wing Dum Height:

_____ mm

Wing:

Wing Angle:

- ☐ 4° ☐ 7° ☐ 10°

Lip Height:

_____ mm

Material:


Screw: ☐ Steel ☐ Titanium

Pinion Gear: ☐ Steel ☐ Aluminium

Shock O-Ring: ☐ O-ring ☐ X-ring ☐ Red ☐ Clear

Chassis:

Ride Height:



Front _____ mm

Rear _____ mm

☐ A ☐ B _____ mm

Tire:

Front

Rear

Tire:

Inserts:

Wheel:

Traction Compound:

Comment :

Electronics:

Battery:

- ☐ Saddle Pack ☐ Short

Battery Position:

- ☐ Std ☐ 8mm Front

Motor Position:

- ☐ Front ☐ Rear

Motor Mount Position:

- ☐ Std ☐ 8mm Front



前

Front

Motor:

Pinion/Spur: