LAZER ZX-5FS SET UP SHEET

KYOSHO — THE FINEST RADIO CONTROL MODELS

Name	Date	Truck	Event
秋元宏太	2012/11/4	谷田部アリーナ	2012年度全日本選手権

Front Suspension



Shock Stay:
- [x] LA216B(SP)
- [ ] LA216HB

Spacer: 1.0 mm



Shock stay hight: 0 mm



Ride Height: 20 mm

Camber Angle: -1.5 °
Toe Angle: out1 °
Sway Bar: none

Front Diff:
- [ ] Rigid
- [ ] Oneway
- [x] Differential, Setting: soft

Spacer: 0 mm



Bump Steer Spacer: -1.0 mm
※LA246ローマウントボールスタッド使用

Caster Block:
- [x] 7°
- [ ] 10°



Bellcrank Spacer: 0.5 mm

Sus. Holder Spacer:

Front [x] / Rear [x]

Steering Tie Rod :
Ball End: In M Out L
23.8mm

Axle-Height Spacer: [ ] Up [x] Down 1.0mm

Rear Suspension



Shock Stay:
- [x] LA217(SP)
- [ ] LA217H

Spacer: 2.0 mm



Shock stay hight: 0



Type-B
Type-B2

Sus. Holder(RF):

[x] IN [ ] OUT E

Sus. Holder(RR):

[ ] IN [x] OUT F



Ride Height: 19 mm

Wing Height:

Camber Angle: -1.5 °
Sway Bar:



0.2mm
2.0mm

Spacer: 2.0 mm

Universal swing shaft:
Born: 62.5mm (UM510,UM510-01)
Wheel shaft: 2本線 (UM522-02)

Wheel Spacer: 0 mm
Axle spacer: IN 0.3 mm

Sus. Holder Spacer:

Front [ ] / Rear [x]

Hub Spacer:
F: 1.0 mm
R: 3.0 mm

Rear Sus. Arm:
- [ ] LA272(UM566,UM521)(SP)
- [ ] UM521-1(1-Hole)
- [ ] LA255
- [x] UM713 (RB6用)

Rear Hub add Toe:
- [ ] 0°Type-B(UM519)
- [ ] 0°Type-B2(UM516-2)
- [x] 0°Alu(UMW516-0)
- [ ] 0.5°Alu(UMW516-05)
- [ ] 1°Alu(UMW516-1)

Shock

	Front	Rear
Shock Piston:	std-5H	std-5H
Shock Oil:	# Losi 37.5	# Losi 32.5
Shock Spring:	Gold	Gold
Limiters:	in mm / out mm	in mm / out 0.5 mm
Shock Length(A):	20 mm	28 mm
Shock Top Type:	[ ] Std:RB5 [ ] Low:ZX5FS	[ ] Std:RB5 [ ] Low:ZX5FS

UM719を使用



A

5.8mm Ball End:
Front: S [x] M [ ] L
Rear: S [ ] M [x] L

Tire

	Front	Rear
Tire:	パンサー ボブキャットクレイ	パンサー スイッチクレイ
Inserts:	プロラインモールド	プロラインモールド
Wheel:	ノーマル	ノーマル
Traction Compound:		

Body/Wing/Other

Body: シュート F:2mm R:6mm down
Wing: Step2.0 前側6mmカット 6mm前方に移動
Lip hight: 21mmカット

Wing Angle: 4° [ ] 7° [ ] 10° [ ]

Battery Post: [ ] Pla [x] Alu

Slipper Type:
- [x] Direct
- [ ] Separates

Slipper Sheet(F-R):
- [ ] Red-White
- [ ] Red-Red
- [x] White-White

Center Post: [ ] Pla [x] Alu

Back bone screw: [ ] F なし [ ] R

Electronics

Motor: ORION VST6.5T
Pinion/Spur: 18T / 78T
Battery: ORION 5500
ESC: Much More FLETA3.0
Radio: FUTABA 4PK Super R
Servo: FUTABA BLS551
Throttle/Brake:
EPA: Expo:
Initial brake:
Drag brake:
Throttle profile:
Steering expo:
Steering speed:

- [x] Smooth
- [ ] Bumpy
- [ ] Low Truction
- [x] Med. Truction
- [ ] Higt Truction
- [ ] Blue Groore
- [x] Clay
- [ ] Sandy
- [ ] Soft Dirt
- [ ] Grass
- [x] wet
- [ ] Dry
- [ ] Dusty
- [ ] Other

Kind in spring

Soft	Pink
	White
	Gold
	Red
	Yellow
	Orange
Hard	Green

Sway Bar

1.0	White
1.1	Pink
1.2	Red
1.3	Orange
1.4	Yellow
1.5	Blue
1.6	Green

Comments

・ボディ：ベルクロで固定
・ウイングスペーサー：上なし/下RB5用-3° &RB6用-3°
・STワイパー（ハード）：接着剤で固定
・STホーン（ハード）：LA221HB使用 ・12ゲージワイヤー
・LAW44ｶｰﾎﾞﾝﾌｧﾊﾞｰﾃﾞｯｷを逆付け ｽﾍﾟｰｻｰ ｾﾝﾀｰ：0.5mm 後：0mm
・ｱｯﾊﾟｰﾃﾞｯｷﾋﾞｽ/ｾﾝﾀｰﾏｳﾝﾄ：ﾁﾀﾝ3x10 STﾎﾞｽﾄ他ﾁﾀﾝ3x8

Ver.1.20