

Event

Technical drawing of a shock absorber assembly. The drawing shows a cross-section of the shock absorber body, which is a cylindrical tube with a coiled spring inside. The assembly includes a mounting bracket on the left and a piston rod with a mounting bracket on the right. Dimension lines indicate measurements in millimeters (mm). One dimension line is labeled 'mm' and points to the length of the shock absorber body. Another dimension line is labeled 'mm' and points to the length of the piston rod.

Technical drawing of a shock absorber assembly. The drawing shows a coiled spring connected to a central rod. The rod has a threaded section on the left and a smooth section on the right. Dimensions are indicated: a vertical dimension of 10 mm for the threaded section, and a horizontal dimension of 10 mm for the smooth section.

☐ Smooth ☐ Dry
☐ Bumpy ☐ Wet
☐ Low Truaction ☐ Dusty
☐ Med. Truaction ☐ Indoor
☐ High Truaction ☐ Outdoor

	16	17	18	19	20	21	22	23	24	25
76		11.18	10.56	10.00	9.50	9.05	8.64	8.26	7.92	7.60
78	12.19	11.47	10.83	10.26	9.75	9.29	8.86	8.48	8.13	7.80

1.0	Nickel
1.1	Gold
1.2	Silver
1.3	Copper
1.4	Black
1.5	Golden
1.6	Chromium