

Name _____

Date _____

Track / City _____

Event _____

Front Suspension

Notes: _____

Spacer: _____ mm

Bellcrank Spacer: _____ mm

Camber Angle: _____ °

Toe Angle: _____ °

Ride Height: _____

Sway Bar: _____

Front Diff
☐ Rigid
☐ Oneway
☐ Differential, Setting: _____

Ball stud position:
☐ Stock
☐ Kingpin

Hub Spacer: _____ mm

Bump Steer Spacer: _____ mm

Knuckle
☐ Standard
☐ Opposite

Axle Height Spacer:
☐ Up
☐ Down

Hex Spacer: _____ mm

Caster Block:
☐ 7°
☐ 10°

Shock Piston: _____

Shock Oil: _____

Shock Spring: # _____

Rear Suspension

Notes: _____

Spacer: _____ mm

Suspension Holder:
☐ BF
☐ BR
☐ A15
☐ A25
☐ A30

Suspension Holder Spacer:
 Front: _____ Rear: _____

Hub Carrier Spacer: _____ mm

Hub Carrier
☐ 2°
☐ 0°

Hex Spacer: _____ mm

Hub Carrier Height
☐ Up
☐ Middle
☐ Down

Wheelbase
☐ Short
☐ Medium
☐ Long

Shock Piston: _____

Shock Oil: _____

Shock Spring: # _____

Sway Bar: _____

Ride Height: _____

Camber Angle: _____ °

Tire

Compound _____

Front Tire _____

Rear Tire _____

Front Inserts _____

Rear Inserts _____

Others

Motor _____

Pinion/Spur _____ / _____

Wing _____

Wing Angle ☐ 0° ☐ 4° ☐ 7°

Center Shaft
☐ Oneway
☐ Direct

Slipper Sheet
☐ Red-White
☐ Red-Red
☐ White-White

Track Condition

☐ Smooth ☐ Dry

☐ Bumpy ☐ Wet

☐ Low Traction ☐ Dusty

☐ Med Traction ☐ Indoor

☐ High Traction ☐ Outdoor

Spring Rate

#50	Black	#68	Blue
#55	Orange	#70	Silver
#60	Orange Yellow	#75	Light Green
#65	Yellow	#80	Green

Gear Ratio

Secondary Gear Ratio 2.5 (16:40)										
	16	17	18	19	20	21	22	23	24	25
76	11.18	10.56	10.00	9.50	9.05	8.64	8.26	7.92	7.60	
78	12.19	11.47	10.83	10.26	9.75	9.29	8.86	8.48	8.13	7.80

Shock Piston

Soft $\longleftrightarrow$ Hard

3-A 2-B 3-B 2-C

Notes: _____

Sway Bar

1.0	Nickel
1.1	Gold
1.2	Silver
1.3	Copper
1.4	Black
1.5	Golden
1.6	Chromium

ESC & Battery

ESC: _____

ESC Settings: _____

Battery: _____

Battery Position:

☐ Front
☐ Rear

Comments