LAZER ZX6 SET UP SHEET

KYOSHO® THE FINEST RADIO CONTROL MODELS

Name _____ Date _____ Truck / City _____ Event _____

Front Suspension:

Shock Position: ① ② ③

Upper Arm Position: ① ② ③

4.8mm Ball Stud:
- ☐ 97050M(Std)
- ☐ UM129

Upper Spacer: ____ mm

Camber ____ ° (- +)

Bump Steer Spacer: ____ mm

Toe:
- ☐ In
- ☐ Out ____ °

Sway Bar:
- ☐ None
- ☐ ____ mm

Spacer: ____ mm

Axle-Height Spacer:
- ☐ Up
- ☐ Down

Caster Block:
- ☐ 7°
- ☐ 10°

Ackerman Spacer: ____ mm

Lower Sus Holder Block:
Front ____ Rear ____

Lower Sus Holder Spacer:
Front ____ mm Rear ____ mm

① ② ③ **Shock Position:**

Wheelbase:
Front ____ mm
Rear ____ mm

Comments: _____

Front Diff:
- ☐ Gear Diff. #____
- ☐ Ball Diff. ____

Rear Suspension:

Shock Position: ① ② ③ ④

Upper Arm Position: ① ② ③

4.8mm Ball Stud:
- ☐ 97050M(Std)
- ☐ UM129

Upper Spacer: ____ mm

Camber ____ ° (- +)

Sus. Arm:
- ☐ LA272(Std)
- ☐ UM713

Hub Carrier: ① ② ③ ④
- Type-B (UM519)
- Type-B2 (UM519-2)

- ☐ 0°Type-B(UM519)
- ☐ 0°Type-B2(UM519-2)
- ☐ 0°Alu(UMW704-0)
- ☐ 0.5°Alu(UMW704-05)
- ☐ 1°Alu(UMW704-1)

Wing Stay Position: ① ② ③

Upper Spacer: ____ mm

Sway Bar:
- ☐ None
- ☐ ____ mm

① ② **Shock Position:**

Lower Sus Holder Block:
Front ____ Rear ____

Toe In: ____ °

UM713 ① ② ③

Lower Sus Holder Spacer:
Front ____ mm Rear ____ mm

Wheelbase:
Front: ____ mm
Rear: ____ mm

Comments: _____

Slipper Type:
- ☐ Separates
- ☐ Direct

Rear Diff:
- ☐ Gear Diff. #____
- ☐ Ball Diff. ____

Shock:

	Front	Rear
Shock Piston:	____	____
Shock Oil:	# ____	# ____
Shock Spring:	____	____
Limiters:	in ____ mm out ____ mm	in ____ mm out ____ mm
Shock Length(A):	____ mm	____ mm

A

Shock Top Type: ☐ Alu(UM719/Std) ☐ UM753-1

5.8mm Ball End:
- Front: ☐ S ☐ M ☐ L
- Rear: ☐ S ☐ M ☐ L

Chassis:

Ride Height:

A B

Front ____ mm

Rear ☐ A ☐ B ____ mm

Electronics:

Battery: ☐ Saddle Pack ☐ Short

Motor Position: ☐ Front ☐ Rear

Servo Mounting: ☐ Straight ☐ Sideways

Motor: ____

Motor Timing: ____

Pinion/Spur: ____

ESC: ____

Radio: ____

Servo: ____

Tire:

	Front	Rear
Tire:	____	____
Inserts:	____	____
Wheel:	____	____
Traction Compound:	____	

Body / Wing:

Body: ____

Wing Mount: ☐ Narrow ☐ Wide

Wing Dum Height: ____ mm

Wing: ____

Wing Angle: ☐ 4° ☐ 7° ☐ 10°

Lip Height: ____ mm

Material:

Screw: ☐ Steel ☐ Titanium

Pinion Gear: ☐ Steel ☐ Aluminium

Shock O-Ring: ☐ O-ring ☐ X-ring ☐ Red ☐ Clear

Comment : _____

Ver.1.00