

LAZER ZX7.5 SET UP SHEET



Name Yousuke Toyoda Date 2026/06/07 Truck / City RC Maniax Arena, Osaka Event TEAM SCHUMACHER JAPAN Off-Road Challenge 2026

Front Suspension:

Shock Position: Upper Arm Position: ① ② ③ ④
Shock Stay: Carbon(Kit) Other

Wheelbase: FR 0 mm FF 2 mm
Bar end position: 2 mm
Sway Bar: None 1.9 mm
Ackerman Spacer: 2 mm

4.8mm Ball Stud: UB049(L:Kit) UB048(M)
Upper Spacer: 1 mm
Caster Block: 7° 13° 10° (Kit) In(Kit) Out

Camber: 2°

Bump Steer Spacer: 1 mm
Toe: In Out 1°

Drive Hub: 4.5mm LAW30GMB(Kit) 5.2mm UB055-52

Front Diff: Ball Diff. Steel Gear Diff. # 10,000 (Kit : LA402) Oil quantity 1.8 g
 Plastic Gear Diff. (LAW87)

Sus. Arm: LA429(Kit) LAW73B(Carbon Comp)

Lower Sus Holder Bush: FF In Out A FR In Out A

Lower Sus Holder Spacer: FF 0.5 mm FR 0.5 mm

Comments:

Rear Suspension:

Shock Position: Wing Stay Position: ① ② ③
Shock Stay: Carbon(Kit) Other

Wheelbase: RF 2 mm RR 0 mm
Bar end position: 4 mm
Sway Bar: None 2.0 mm

4.8mm Ball Stud: UB047(S:Kit) UB048(M) UB046(Low:-1mm)

Upper Spacer: 1.5 mm
Joint Position: IN (Kit) OUT

Camber: 2°

Hub. Spacer: 2 mm
Drive Hub: 4.5mm LAW30GMB(Kit) 5.2mm UB055-52 6.2mm UB055-62

Sus. Arm: UB027(Kit) UBW009(Carbon Comp)

Lower Sus Holder Bush: RF In Out E RR In Out B

Toe In: 2.7°

Lower Sus Holder Spacer: RF 1 mm RR 1 mm

Comments:

Shock:

	Front	Rear
Shock Piston:	<u>2-1.8</u>	<u>2-1.9</u>
Shock Oil:	# <u>400</u>	# <u>350</u>
Shock Spring:	<u>5dot 4.0</u>	<u>4dot 2.2</u>
Limiters:	in <u>3</u> mm out mm	in mm out mm
Shock Length (A):	<u>20</u> mm	<u>28</u> mm

O-ring: ORG03XB(Clear) ORG03XRB(Red) Other

Ball End:
Front: S M L
Rear: S M L

Spring Sheet:
Front: Rear:

Chassis:

Screw: Titanium Steel

Front 14 mm **Rear** 14 mm

Ride Height:

Center Bulk: Front (Kit) Rear **Battery Location:** Front (Kit) Rear

Tire: Front U6855 Cactus F Rear U6838 Cactus R
Compound: Yellow Yellow
Inserts: U6738 Inner 2WD Front U6733 Inner 4WD Front
Wheel: Kit(5mm Hole) Kit(5mm Hole)
Note: Front outer glue

Carbon Lower Brace: LAW85
 Front Rear

Front Upper Plate:

Electronics:
Motor: HW 13.5 G4R
Pinion / Spur: 24 / 72
Pinion Gear: Steel Alum
Battery: TRION 4700/7.6V/130C
ESC: HWXeRUN XR10 PRO G2S
Radio: FUTABA T10PX
Servo: FUTABA HPS-CT702

Body / Wing:

Body: ZX7-LW(LAB07LWB)

Wing Hole Position: 29 mm

Wing Dum Height: _____ mm

Wing: _____ mm
KIT(RB7.5)

Lip Height: _____ mm

Wing Angle: 4° 7° 10°

Comments:

Truck Condition

Surface: Smooth Sandy Bumpy
Type: Soft Dirt Clay Carpet
 Astro Grass

Condition: Blue Groove Hard Packed
 Glued Dry Smei Dry Dusty Wet
 Higt Truaction Med. Truaction Low Truaction

Comment :

Kit parts and opt parts
 Settings and parts other than those specified in the kit.