



Name:		Date:	Date: Event:				
City: State:		Track:					
	☐ Hard Packed ☐ Blue Groove	•	☐ Low Bite	☐ High Bite			
	□ Loose/Loamy □ Dry	☐ Wet ☐ Dusty		Other			
Front Suspension	Differentials		Ackerr	man	Bump Steer		
Toe:	Front: Standard Smart		Long	<u></u>	Up Down		
Ride Height:	Spring Wire Dia:		Shor		ор Боші	3 2	
Camber:	_ Qty of Springs:			(4)		1 ———	
Caster:	Ramp Plate:						
Wheel Hex:							
Sway Bar:	_ Diff Fluid:			a	┌ Outsi	3 - (3)	
Piston/Oil:	- Conton Dotardard Dona		(F		Insi		
Limiter/Droop:	- Center: □ Standard □ Sma - Spring Wire Dia:						
Overall Shock Length:	' •						
Steering Ackerman:							
Bump Steer:	· ·						
Camber Link:				5			
Shock Location:	_		26	≫ ⁄			
Receiver Battery Type:	-		Notes:				
Rear Suspension							
Roll Center: HRC LRC							
Toe:		\	Wing Setup				
Anti-Squat:			Ving Type:		3.0		
Ride Height:		— v	Ving Spacer	: □.250	□ .500		
Camber:		V	Vicker Bill:	□ .250 □	.350		
Rear Hub Spacing:		$-\vdash$			 3—		
Wheel Hex: Sway Bar:				DСВА	2— 1—		
Piston/Oil:		_		1111		5—	
Spring:						3 3	
Limiter/Droop:				0000	Outoido	1——————————————————————————————————————	
Overall Shock Length:					┌ Outside ┌ Inside		
Camber Link:				1		(0)	
Shock Location:					101		
Rear Diff Fluid:						0 0 1	
Electronics			ــــــــــــــــــــــــــــــــــــــ	 			
	nyo Evno:		Notes:				
Radio: Ser	rvo Expo: otor:						
ESC: Pin							
Initial Brake: Sp							
Drag Brake: Bat		Tires	Туре		Compound	Insert	
Throttle Profile:	у		•		Compound		
Timing Advance:							
Throttle/Brake Expo:							
Throttle/Brake EPA:		Notes: .					