



SETUP SHEET

Driver: Ellis Stafford

Date: April 04

Track: Holbeach grass

☐ Indoor	☒ Smooth	☒ Slippery
☒ Outdoor	☐ Rough	☐ High-Bite
☐ Tight / ☒ Open		☐ Blue-Groove

FRONT SUSPENSION (Circle or Check the Appropriate Settings)

Toe ☒ In 0
☐ Out 1

Ride Height Arms Level

Camber ☒ - 0
☐ + 1

Caster ☒ Stock 0
☐ Other _____

Sway Bar ☐ Yes size: _____
☒ No

of washers under steering/tie-rod ball studs

Spindle ball stud: 1

Bellcrank ball stud: 0

Spindle Location

☒ Top
☐ Middle
☐ Bottom

☐ A
☒ B

Axle Spacer

☒ Narrow - inside
☐ Wide - outside

☐ Inside
☒ Middle
☐ Outside

☒ 1
☐ 2
☐ 3

Front Shocks

Oil: 30 wt

Piston: Red ☒ Standard / ☐ Drilled

Spring: Green Internal: ☐ Yes / ☒ No

Limiters ☐ Inside- _____ ☐ Outside- _____

REAR SUSPENSION

Body: BK2

Wing: BK2

Toe-In ☒ Inside Std 0
☐ Outside _____

Front Wing: ☐ Yes / ☒ No

☒ No Shim

Pivot Support ☐ Shim Under Front — # of shims: _____

Ride Height Drive shaft just below level

Camber ☒ - 0
☐ + 1

Drive Shafts ☒ Dogbones ☐ Aluminum
☐ CVDs ☒ Steel

Rear Hub Spacing ☐ Forward
☒ Center
☐ Rear

Sway Bar ☒ No
☐ Yes size: _____

Rear Shocks

Oil: 25 wt

Piston: Red ☒ Standard / ☐ Drilled

Spring: Red Internal: ☐ Yes / ☐ No

Limiters: ☐ Inside - _____ ☐ Outside - _____

Wing Position

☒ Forward
☐ Back

Wing Mount

☐ Top
☒ Bottom

☐ 4
☐ 3
☒ 2
☐ 1

☒ 1
☐ 2
☐ 3

☐ Outside
☒ Middle
☐ Inside
☒ Long
☐ Short
☒ A
☒ B
☒ Long
☐ Short
☒ Outside
☐ Inside

Tires

Front: Slim Mini

Rear: Minispikes

Compound

Yellow

Yellow

Foam

Hard

Soft

Motor: 10 x 2 Pinion/Spur: 23 / 78

Battery Position: Forward

Weather Conditions/Notes: Dry