



Name:	Date: Event:
City: State:	Track:
Track Indoor Tight Smooth Hard Packed Blue Groove Conditions Outdoor Open Rough Loose/Loamy Dry	re
Front Suspension	Ackerman
Toe:	— Ackerman
Ride Height:	
Camber:	
Caster: □10° □15° □20°	
Sway Bar:	
Oil:	Inside 5
Piston:	
Spring: ☐ Standard ☐ Low Freq. Color:	
Shock Limiters:	
Shock Location:	
Bump Steer Ball Stud: ☐ Standard ☐ Low Mount	Notes:
Bumper Steer Spacers:	
Camber Link:	
Ackermann:	
Rear Suspension	
Toe:	
Anti-Squat:	
Roll Center: Low Roll Center (LRC) High Roll Center	(HRC) 3 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
Ride Height:	
Camber:	
Rear Hub Spacing:	C B A
Hex Width:	
Sway Bar:	Outside Inside
Oil:	
Piston:	
Spring: ☐ Standard ☐ Low Freq. Color:	
Shock Limiters:	(° 3.0
Camber Link:	
Shock Locations:	
Wing/Wickerbill:	mining Advance.
Battery Position:	Radio: Throttle/Brake Expo: Servo: Servo Expo:
	ESC: Throttle/Brake EPA:
	Initial Brake: Motor: Spur:
	Throttle Profile: Battery:
Compound Insert	
ires	
Front:	
Rear:	
Notes:	