



Name:	Date:	e: Event:			
City: State:	Track:				
Track ☐ Indoor ☐ Tight ☐ Smooth ☐ Hard Packed ☐ Blue Groove Conditions ☐ Outdoor ☐ Open ☐ Rough ☐ Loose/Loamy ☐ Dry	e	☐ Grass ☐ Astro Turf	☐ Low Bite☐ Med Bite	☐ High Bite☐ Other	
Front Suspension					
Toe:		Ackerm	an Man		
Ride Height:		<b>Y</b> )			2
Camber:	(	A-			
Caster: □10° □15° □20°	"	<b>y</b>			
Sway Bar:			SPACER	—Outside	2
Oil:			_/	Inside	5
Piston:	<b></b>	7000	$\geq$		
Spring: ☐ Standard ☐ Low Freq. Color:	—-Ч				10 4 3
Shock Limiters:					
Shock Location:					
Bump Steer Ball Stud: 🔲 Standard 🚨 Low Mount		TLR331012	2 Aluminum	Servo Mo	unt
Bumper Steer Spacers:		TLR334007	' Aluminum	Front Spir	ndle
Camber Link:	□	TLR334009	Aluminum	Steering I	Bellcrank
Ackermann:					
Notes:					
Rear Suspension					
Toe:					
Anti-Squat:				4 ′ 3 -	
Roll Center: Low Roll Center (LRC) High Roll Center (				2 - 1 -	
Ride Height:					
Camber:		С	ВА		
Rear Hub Spacing:		Ī	ĪĪ		2
Hex Width:			Outsid		
Sway Bar:Oil:			Inside		5_4
Piston:					43
Spring: ☐ Standard ☐ Low Freq. Color:				//	
Shock Limiters:					(0 3.0
Camber Link:		TLR334008	Aluminum R	tear Hub	
Shock Locations:		4			
Wing/Wickerbill:	Elec	etronics o:			ce:
Battery Position:		o:			
Notes:				-	EPA:
		l Brake:			
	_	Brake: ttle Profile:			Spur:
Tires		mpound			Additive
Front:		podiid			
Rear:			_		
Notes:					