

Name: _____ Date: _____ Track: _____	Track Conditions Size: ☐ Open ☐ Med. ☐ Tight Traction: ☐ High ☐ Med. ☐ Low Surface: ☐ Smooth ☐ Med. ☐ Bumpy	Result Race Time / Lap: _____ Best Lap (1Lap): _____
---	--	---

Front Suspension 	Ride Height: _____ Toe Angle: _____ Kingpin Ball Spacer(Upper): _____ (Lower): _____ Wheel Hub: _____ Anti Roll Bar: _____ Upper Arm Spacer: _____ Lower Arm Spacer: _____ Lower Arm Position (Kick Up): _____
-----------------------------	--

Front Shocks 	Piston: _____ Oil: _____ Spring: _____ Shock Position: _____ Pivot Ball Position: ☐ Front ☐ Rear Damper Stay: ☐ E2502(Aluminum) ☐ E2511(CFRP)
-------------------------	---

Rear Suspension 	Ride Height: _____ Camber Angle: _____ Wheel Hub: _____ Anti Roll Bar: _____ Lower Arm Spacer: _____ Upright Spacer: _____ Upright: ☐ E2131 ☐ Other _____ Lower Arm Position (Toe Angle): _____
----------------------------	---

Rear Shocks 	Piston: _____ Oil: _____ Spring: _____ Shock Position: _____ Pivot Ball Position: ☐ Front ☐ Rear Damper Stay: ☐ E2522(Aluminum) ☐ E2523(CFRP)
------------------------	---

Engine Type: _____ Plug: _____ Gasket: _____ Reducer: _____ Muffler: _____ Fuel: _____ Engine Mount: ☐ E0701(Standard) ☐ E2701(One Piece)	Diff. Oil Front: _____ O-Ring: _____ pcs. Center: _____ pcs. Rear: _____ pcs.
--	---

Tires Type: _____ Compound: _____ Inserts: _____ Wheel: _____	Front _____ _____ _____ _____	Rear _____ _____ _____ _____
--	--	---

Clutch Clutch Bell: _____ Spur Gear: _____ Clutch Shoes: _____ Clutch Spring: _____

Body/Wing Body: _____ Wing: _____
--

Comments _____ _____ _____ _____
