

Driver : _____
Date : _____
Track : _____
Event : _____

Track Condition
Size : Open ☐ Mixed ☐ Tight ☐
Traction : High ☐ Medium ☐ Low ☐
Condition : Smooth ☐ Bumpy ☐ Dry ☐ Wet ☐
Dusty ☐ Grooved ☐ Hard Packed ☐

Front Suspension

Shock Tower
Alu. ☐ CFRP ☐

Upper: Alu. ☐ Steel ☐
Lower: Alu. ☐ Steel ☐

Upper Ball Spacer mm _____

Bump Spacer mm _____

Lower Arm Spacer mm _____

Front Link Mount

Front Arm Mount F

Front Arm Mount R

Caster Spacer mm _____

Ball Position : Forward ☐ Back ☐

Lower Arm Spacer mm _____

Lower Arm Plate

Lower Arm Type
STD. ☐ LW. ☐

Upper: Alu. ☐ Steel ☐
Lower: Alu. ☐ Steel ☐

Wheel Hex

Upright Type
0 ☐ 1.5 ☐

Ride Height : _____ Toe : _____ °
Anti-Roll Bar : ϕ _____
F Upright Arm : 0 Dot ☐ 1 Dot ☐
Drive Shaft : CVA ☐ Universal ☐
Chassis Brace : Short ☐ Long ☐
Servo Saver Arm : STD. ☐ Alu. ☐
Servo Horn : STD. ☐ Alu. ☐
Size : _____

Rear Suspension

Shock Tower
Alu. ☐ CFRP ☐

Rear Arm Mount F

Rear Arm Mount R

Lower Arm Spacer mm _____

Lower Arm Type
STD. ☐ LW. ☐

Hub Spacer mm _____

Link Spacer mm _____

Lower Arm Plate

Ball Position : Forward ☐ Back ☐

Wheel Hex

Ride Height : _____ Camber : _____ °
Rear Hub : Plastic ☐ Alu. ☐
Anti-Roll Bar : ϕ _____
Drive Shaft : CVA ☐ Universal ☐
Rear Link Plate : 1Dot ☐ 3Dot ☐
Dot Orientation : In ☐ Out ☐

Shocks		Front	Rear	Differential		Front	Center	Rear
 Length	Piston			42T/12T ☐	Oil			
	Oil			44T/13T ☐	Center Drive Shaft	Dog Bone ☐		Dog Bone ☐
	Spring					Universal ☐		Universal ☐
	Bladder	☐	☐	Clutch & Gearing		Spur Gear T		Bell T
	Emulsion	☐	☐			Spring Position: Dot ☐ Non Dot ☐		3Pin ☐ 4Shoe ☐
Length			Shoe : _____					
Notes			Spring : _____					
Engine		Body & Wing		Tire	Front		Rear	
Type		Body		Type				
Muffler		Wing		Compound				
Manifold		Front Wing		Inserts				
Fuel		Gap to Tower		Wheel				
Reducer				Chassis Weight Front : _____ g Rear : _____ g				
Grow Plug				Notes				
Engine Mount : STD. ☐ 1pcs. ☐								