

Driver : **Carpet**
 Date : _____
 Track : **Futaba Buggy Tract**
 Event : _____

Track Condition
 Size : Open Med. Tight
 Traction : High Med. Low
 Condition : Smooth Bumpy Dry Wet
 Dusty Grooved Hard Packed

Ver. 2110N

Front Suspension

Shock Tower
 Alu. CFRP

Upper: Alu. Steel
 Lower: Alu. Steel

Upper Ball Spacer **1** mm
 Caster Spacer **2** mm
 Bump Spacer **2** mm
 Lower Arm Spacer **1** mm

Ball Position : Forward Back
 Lower Arm Spacer **1** mm

Lower Arm Plate **CFRP**
 Lower Arm Type **STD.** LW.

Upper: Alu. Steel
 Lower: Alu. Steel

Wheel Hex **+1**
 Upright Type **0** 1.5

Ride Height : 22mm	Toe : Out 1°
Anti-Roll Bar : Φ2.5	
F Upright Arm : 0 Dot <input checked="" type="checkbox"/> 1 Dot <input type="checkbox"/>	
Drive Shaft : CVA <input checked="" type="checkbox"/> Universal <input type="checkbox"/>	
Chassis Brace : Short <input checked="" type="checkbox"/> Long <input type="checkbox"/>	
Servo Saver Arm : STD. <input checked="" type="checkbox"/> Alu. <input type="checkbox"/>	
Servo Horn : STD. <input type="checkbox"/> Alu. <input checked="" type="checkbox"/>	
Size : 18.5mm	

Rear Suspension

Shock Tower
 Alu. CFRP

Lower Arm Spacer **0** mm
 Lower Arm Type **STD.** LW.

Hub Spacer **2.5** mm
 Link Spacer **3** mm

Ball Position : Forward Back

Lower Arm Plate **CFRP**
 Wheel Hex **+1**

Ride Height : 27mm	Camber : 2.5°
Rear Hub : Plastic <input checked="" type="checkbox"/> Alu. <input type="checkbox"/>	
Anti-Roll Bar : Φ2.9	
Drive Shaft : CVA <input checked="" type="checkbox"/> Universal <input type="checkbox"/>	
Rear Link Plate : 1Dot <input checked="" type="checkbox"/> 3Dot <input type="checkbox"/>	
Dot Orientation : In <input type="checkbox"/> Out <input checked="" type="checkbox"/>	

Shocks	Front		Rear		Differential		Front	Center	Rear
	 Piston MIP 1.2x8 Oil #500 Spring 9.0x70 Bladder <input type="checkbox"/> Emulsion <input checked="" type="checkbox"/> Length 104mm Notes : Valve Blue Or 1.3x8 F:600/R:550	MIP 1.2x8		MIP 1.2x8		42T/12T <input checked="" type="checkbox"/>	Oil	10,000	10,000
				44T/13T <input type="checkbox"/>	Center Drive Shaft	Dog Born <input checked="" type="checkbox"/>		Dog Born <input checked="" type="checkbox"/>	
						Spur Gear 46 T		Bell 13 T	
						Spring Position: Dot <input checked="" type="checkbox"/> Non Dot <input type="checkbox"/>	3Pin <input type="checkbox"/>	4Shoe <input checked="" type="checkbox"/>	
						Shoe : Aluminium x 2 / Carbon x 2			
						Spring : 0.95 x 4			

Engine		Body & Wing		Tire	Front	Rear
Type		Body		Type	Proline Fugitive	Proline Fugitive
Muffler		Wing		Compound	S4	S4
Manifold		Front Wing		Inserts		
Fuel		Gap to Tower		Wheel		
Reducer		1 <input type="checkbox"/> 2 <input type="checkbox"/> 3 <input type="checkbox"/> 4 <input checked="" type="checkbox"/>	Chassis Weight Front : 0 g Rear : 0 g			
Grow Plug			Notes			
Engine Mount : STD. <input type="checkbox"/> 1pcs. <input checked="" type="checkbox"/>						