

Driver : _____
 Date : _____
 Track : _____
 Event : _____

Track Condition
 Size : Open ☐ Med. ☐ Tight ☐
 Traction : High ☐ Med. ☐ Low ☐
 Condition : Smooth ☐ Bumpy ☐ Dry ☐ Wet ☐
 Dusty ☐ Grooved ☐ Hard Packed ☐

Front Suspension

Shock Tower
 Alu. ☐ CFRP ☐

Upper: Alu. ☐ Steel ☐
Lower: Alu. ☐ Steel ☐

Upper Ball Spacer mm

Front Link Mount 1 2 3 4 5 6 7 8 9 ☐

Front Arm Mount F ☐

Front Arm Mount R ☐

Caster Spacer mm

Ball Position: Forward ☐ Back ☐

Lower Arm Spacer mm

Lower Arm Plate

Lower Arm Type
 STD. ☐ LW. ☐

Upper: Alu. ☐ Steel ☐
Lower: Alu. ☐ Steel ☐

Bump Spacer mm

Wheel Hex

Upright Type
 0 ☐ 1.5 ☐

Ride Height : _____ **Toe :** _____

Anti-Roll Bar :

F Upright Arm : 0 Dot ☐ 1 Dot ☐

Drive Shaft : CVA ☐ Universal ☐

Chassis Brace : Short ☐ Long ☐

Servo Saver Arm : STD. ☐ Alu. ☐

Servo Horn : STD. ☐ Alu. ☐

Size : _____

Rear Suspension

Shock Tower
 Alu. ☐ CFRP ☐

Rear Arm Mount F 1 2 3 4 5 6 ☐

Rear Arm Mount R 1 2 3 4 5 6 7 8 9 ☐

Lower Arm Spacer mm

Lower Arm Type
 STD. ☐ LW. ☐

Hub Spacer mm

Link Spacer mm

Lower Arm Plate

Ball Position: Forward ☐ Back ☐

Wheel Hex

Ride Height : _____ **Camber :** _____

Rear Hub : Plastic ☐ Alu. ☐

Anti-Roll Bar :

Drive Shaft : CVA ☐ Universal ☐

Rear Link Plate : 1Dot ☐ 3Dot ☐

Dot Orientation : In ☐ Out ☐

Shocks

Front

Rear

Differential

Front

Center

Rear



Piston
 Oil
 Spring
 Bladder
 Emulsion
 Length
 Notes :

42T/12T ☐

Oil

44T/13T ☐

Center

Drive Shaft

Dog Born ☐

Universal ☐

Dog Born ☐

Universal ☐

Clutch & Gearing

Spur Gear

T

Bell

T

Spring Position: Dot ☐ Non Dot ☐

3Pin ☐

4Shoe ☐

Shoe :

Spring :

Engine

Body & Wing

Tire

Front

Rear

Type

Muffler

Manifold

Fuel

Reducer

Grow Plug

Engine Mount :


STD. ☐ 1pcs. ☐

Body

Wing

Front Wing

Gap to Tower



Type

Compound

Inserts

Wheel

Chassis Weight

Front :

g

Rear :

g

Notes