


SETUP SHEET

Track Conditions



Name :	Composition _____		
Date :	Traction: ☐ High	☐ Med.	☐ Low
Track :	Surface: ☐ Smooth	☐ Med.	☐ Bumpy

Front Suspension



Toe _____
 Camber _____
 Caster 0° 4° 5° _____
 Ride height _____

Bumpsteer shim _____




Oil _____
 Spring _____
 Piston _____
 Limiter - In _____ /Out _____
 Preload _____
 Notes _____



☐ +3°

☐ +0°




☐ +3°

☐ +0°

☐ +5mm

☐ +5mm, 7°, 66gr

Ackermann



Front _____ Rear _____



☐ 1.5mm


☐ 1.6mm

Tire _____

Wheel _____


Inserts _____

Rear Suspension



Camber _____
 Ride height _____


Shim _____




Hex

☐ 3.2mm

☐ 4mm




Oil _____
 Spring _____
 Piston _____
 Limiter - In _____ /Out _____
 Preload _____
 Notes _____



Anti-Squat ☐ 0

☐ 1

☐ 2






Toe-in


☐ 3°

☐ 3.5°

☐ 4°




Front _____ Rear _____



☐ Gear differential

Ball differential ☐



Tire _____

Wheel _____

Inserts _____

Diff Oil # _____

Other

Configuration ☐ Rear Motor ☐ Midship ☐ 3 Idler ☐ 4 Idler

Motor _____ Body _____ Wing _____

ESC _____ Setting _____