


Track Conditions


Name :	Composition _____		
Date :	Traction: ☐ High	☐ Med.	☐ Low
Track :	Surface: ☐ Smooth	☐ Med.	☐ Bumpy

Front Suspension





Toe _____
 Camber _____
 Caster 0° 3° 4° 5° _____
 Ride height _____


Bumpsteer shim _____



Oil _____
 Spring _____
 Piston _____
 Limiter - In _____ /Out _____
 Preload _____
 Notes _____




Front _____ Rear _____



☐ +3°
☐ +0°


Ackermann



☐ +5mm

☐ +5mm, 7°, 66gr

☐ 1.5mm
☐ 1.6mm




Tire _____

Wheel _____


Inserts _____

Rear Suspension




Camber _____
 Ride height _____



Shim _____



Hex
☐ 3.2mm
☐ 4mm




Oil _____
 Spring _____
 Piston _____
 Limiter - In _____ /Out _____
 Preload _____
 Notes _____





Anti-Squat ☐ 0
☐ 1
☐ 2

Toe-in

☐ 2.5°
☐ 3°
☐ _____




Front _____ Rear _____



☐ Gear differential

Ball differential ☐



Diff Oil # _____

Tire _____

Wheel _____

Inserts _____

Other

Configuration ☐ Rear Motor ☐ Midship ☐ 3 Idler ☐ 4 Idler

Motor _____ Body _____ Wing _____

ESC _____ Setting _____