


Track Conditions



Name :	Composition _____		
Date :	Traction: ☐ High	☐ Med.	☐ Low
Track :	Surface: ☐ Smooth	☐ Med.	☐ Bumpy

Front Suspension



Toe _____
 Camber _____
 Caster 0° 4° 5° _____
 Ride height _____

Bumpsteer shim _____



Oil _____


Spring _____

Piston _____


Limiter - In /Out _____

Preload _____

Notes _____

☐ +3°☐ +0°☐ +3°☐ +0°☐ +5mm☐ +5mm, 7°, 66gr

Ackermann



Front Rear



1.5mm


1.6mm

Tire _____

Wheel _____


Inserts _____

Rear Suspension




Camber _____
 Ride height _____

Shim _____



Hex

☐ 3.2mm☐ 4mm

Oil _____

Spring _____

Piston _____




Limiter - In /Out _____

Preload _____



Notes _____

Anti-Squat ☐ 0☐ 1☐ 2

Toe-in

☐ 3°☐ 3.5°☐ 4°

Front Rear

☐ Gear differentialBall differential ☐

Tire _____

Wheel _____

Inserts _____

Diff Oil # _____

Other

Configuration ☐ Rear Motor ☐ Midship ☐ 3 Idler ☐ 4 Idler

Motor _____ Body _____ Wing _____

ESC _____ Setting _____