Front Suspension	Camber	° Toe		Poar S	uspension		<u> </u>	Shock Oil	
i Tonic Guspension	Caster	° Ride He	iaht	Kear 3	uspension			^證 震油 #	
0	<u> </u>		.9	m				Shock Piston ^醛 震活塞	
							_	Spring	
		7-11		m	nm The Control of the			彈簧 Preload	
o o o o o o	ar 🗀	9-0					TT <u>6</u>	句下高度	mm
			C S					Limiters Inside	mm
Front				7000	00/			Outside	mm
0 0 1mm				10-		무무		Location Front□	Rear 🗌
╏└□ 2mm (FF)	mm						<u> </u>		rtoui 🗀
(11)	9 4		D					Camber	
			O					Ride Height	
				(RF)	<u>い</u> 1mm □ 2mm _{□ 2.5}				
		mm		<u> </u>		,	[
Shock Oil									
<u> </u>			mm		mm			Heave /	
Shock Piston 避農活塞						Г	¬ 1		
Spring		Comment	s	l l		Gear 齒輪	r Diff		
彈簧 Preload						西 輌	差迷 "		
向下高度	mm								1,21
Limiters Inside	mm					Slip	ner [
Outside	mm	Diff	Front	Center	Rear				
		Oil							
Tires & Wheels		Weath		Track Condit		Others			
	lear		S	Size: □ Open □	Med ☐ Tight	ESC			
Tire Ti 輪胎 輪	re 胎	Temperature /溫度		raction: High	action: □ High □ Med □ Low 低				
Wheel W	heel 框					馬達 / Botton/			
	sets 海綿	_	Surfac		e: □Smooth □ Med □ Bumpy 電池 Battery				
	海師 Otes	□Cla		=	osition: Astroturf Carpet		Pinion/Spur 馬達齒/齒輪		
]Clay □Dirt □G					
]Other:		Wing			