

Driver and Event	
Name	Tom Cockerill
Date	November '13
Event	BWT Rd 2 at BCA, Belgium
Weather	Indoors
Result	Win

Track Conditions	
Surface	AstroTurf
Grip Level	Medium
Track Condition	Smooth, Jumps, Dusty



Electrics and Gearing	
E.S.C	Nosram Comet HD
Servo	Sanwa
Receiver	KO
Batteries	Nosram 5800 Saddle
Motor	Nosram Pure 2 6.5
Spur Gear	98T <input checked="" type="checkbox"/> 95T <input type="checkbox"/>
Pinion	19
LH Cell Position	Forward <input checked="" type="checkbox"/> Backward <input type="checkbox"/>

Wheels and Tyres	
Rear Wheels	Schumacher FlexLite
Rear Tyre	Schumacher MiniSpike
Rear Insert	Schumacher Medium
Front Wheels	Schumacher FlexLite
Front Tyre	Sch Slim MiniSpike
Front Insert	Schumacher Medium

Additional Settings	
Car Weight	1670
Weights Added	None
Chassis	Alloy <input type="checkbox"/> Option <input checked="" type="checkbox"/>

**NOTES**  
 Core RC Springs & Oil  
 Big Bore Shocks  
 Cougar rear Arms (Longest WB)  
 Carbon Chassis

Diff Type	
Front	Ball <input type="checkbox"/> Gear <input checked="" type="checkbox"/>
Rear	Ball <input type="checkbox"/> Gear <input checked="" type="checkbox"/>
	Diff Oil
	7,000
	10,000

Rear Shocks	
Oil	500
Spring	Red
Piston	2 Hole
Drilled	<input checked="" type="checkbox"/>
Hole Size	1.80 mm
Shock Length	96.6 mm

Front Shocks	
Oil	600
Spring	Red
Piston	2 Hole
Drilled	<input checked="" type="checkbox"/>
Hole Size	1.70 mm
Shock Length	82.0 mm

Rear Suspension	
Anti roll bar	No <input checked="" type="checkbox"/> 1.00 <input type="checkbox"/> 1.20 <input type="checkbox"/> 1.40 <input type="checkbox"/> 1.60 <input type="checkbox"/>
Wheelbase	Short <input type="checkbox"/> Med <input type="checkbox"/> Long <input checked="" type="checkbox"/>
Rear Toe-in & Track Washers	0.00 Difference = 0.00° Toe-in <input type="checkbox"/> 0.50 Difference = 0.60° Toe-in <input type="checkbox"/> 1.00 Difference = 1.30° Toe-in <input type="checkbox"/> 1.50 Difference = 1.95° Toe-in <input type="checkbox"/> 2.00 Difference = 2.60° Toe-in <input type="checkbox"/> 2.50 Difference = 3.25° Toe-in <input checked="" type="checkbox"/> 3.00 Difference = 3.90° Toe-in <input type="checkbox"/>
Rear	0 mm
Front	0 mm
Blocks	Moulded <input checked="" type="checkbox"/> Alloy <input type="checkbox"/>

Camber at Ride Height	-2.0 Deg
Ride Height	20 mm
Anti-squat Washers	
0.00 Difference = 0.00° Toe-in	<input type="checkbox"/>
0.50 Difference = 0.60° Toe-in	<input type="checkbox"/>
1.00 Difference = 1.30° Toe-in	<input type="checkbox"/>
1.50 Difference = 1.95° Toe-in	<input type="checkbox"/>
2.00 Difference = 2.60° Toe-in	<input checked="" type="checkbox"/>
2.50 Difference = 3.25° Toe-in	<input type="checkbox"/>
3.00 Difference = 3.90° Toe-in	<input type="checkbox"/>
Rear	N/A mm
Front	N/A mm
Link Washers	3.0 mm
Pin High	R <input checked="" type="checkbox"/> F <input checked="" type="checkbox"/>
Pin Low	<input type="checkbox"/>

Front Suspension	
Anti roll bar	No <input checked="" type="checkbox"/> 1.00 <input type="checkbox"/> 1.20 <input type="checkbox"/> 1.40 <input type="checkbox"/> 1.60 <input type="checkbox"/>
Track Washers	1.0 mm
Blocks	Moulded <input type="checkbox"/> Alloy <input checked="" type="checkbox"/>

Camber at Ride Height	-2.0 Deg
Ride Height	20 mm
Toe-In	-1.0 Deg
Washers	1.0 mm
Link Washers	0 mm
Front Rake	10.0 Deg <input checked="" type="checkbox"/> 7.5 Deg <input type="checkbox"/>
Front Yoke	12.5 <input type="checkbox"/> (10.0) <input type="checkbox"/> 7.5 <input checked="" type="checkbox"/>