

Driver and Event	
Name	Tom Cockerill
Date	Feb '13
Event	Motorama
Weather	N/A
Result	5th

Track Conditions	
Surface	Clay
Grip Level	Medium
Track Condition	Smooth, Slight Groove



Electrics and Gearing	
E.S.C	Speed Passion Reventon Pro
Servo	GM
Receiver	KO
Batteries	Speed Power 4200
Motor	Speed Passion 6.5
Spur Gear	98T <input checked="" type="checkbox"/> 95T <input type="checkbox"/>
Pinion	20
LH Cell Position	Forward <input checked="" type="checkbox"/> Backward <input type="checkbox"/>

Wheels and Tyres	
Rear Wheels	Schumacher FlexLite
Rear Tyre	JC Green Barcode
Rear Insert	AKA
Front Wheels	Schumacher FlexLite
Front Tyre	JC Green Barcode
Front Insert	AKA

Additional Settings	
Car Weight	
Weights Added	None
Chassis	Alloy <input type="checkbox"/> Option <input checked="" type="checkbox"/>

NOTES
 CF Chassis
 Spec R Front Driveshafts
 CoreRC Oil & Springs
 Big Bore Shocks
 2.0mm Ackerman Spacing

Diff Type	
Front	Ball <input checked="" type="checkbox"/> Gear <input type="checkbox"/>
Rear	Ball <input checked="" type="checkbox"/> Gear <input type="checkbox"/>

Rear Shocks	
Oil	300
Spring	Red
Shock Cap Sealed	<input type="checkbox"/>
Vented	<input type="checkbox"/>
Emulsion	<input checked="" type="checkbox"/>
Piston	2 hole
Drilled	<input checked="" type="checkbox"/>
Hole Size	1.70 mm
Shock Length	96.1 mm

Front Shocks	
Oil	300
Spring	Red
Shock Cap Sealed	<input type="checkbox"/>
Vented	<input type="checkbox"/>
Emulsion	<input checked="" type="checkbox"/>
Piston	2 Hole
Drilled	<input checked="" type="checkbox"/>
Hole Size	1.70 mm
Shock Length	83.5 mm

Rear Suspension	
Anti roll bar	No <input checked="" type="checkbox"/> 1.00 <input type="checkbox"/> 1.20 <input type="checkbox"/> 1.40 <input type="checkbox"/> 1.60 <input type="checkbox"/>
Wheelbase	Short <input type="checkbox"/> Med <input checked="" type="checkbox"/> Long <input type="checkbox"/>

Camber at Ride Height	-0.5 Deg
Ride Height	21 mm
Anti-squat Washers	
0.00 Difference = 0.00° Toe-in	<input type="checkbox"/>
0.50 Difference = 0.60° Toe-in	<input type="checkbox"/>
1.00 Difference = 1.30° Toe-in	<input type="checkbox"/>
1.50 Difference = 1.95° Toe-in	<input type="checkbox"/>
2.00 Difference = 2.60° Toe-in	<input checked="" type="checkbox"/>
2.50 Difference = 3.25° Toe-in	<input type="checkbox"/>
3.00 Difference = 3.90° Toe-in	<input type="checkbox"/>

Rear Toe-in & Track Washers	
0.00 Difference = 0.00° Toe-in	<input type="checkbox"/>
0.50 Difference = 0.60° Toe-in	<input type="checkbox"/>
1.00 Difference = 1.30° Toe-in	<input type="checkbox"/>
1.50 Difference = 1.95° Toe-in	<input type="checkbox"/>
2.00 Difference = 2.60° Toe-in	<input type="checkbox"/>
2.50 Difference = 3.25° Toe-in	<input type="checkbox"/>
3.00 Difference = 3.90° Toe-in	<input checked="" type="checkbox"/>
Rear	0.5 mm
Front	0 mm

33.5 (1 Dink)	<input type="checkbox"/>
38.0 (2 Dink)	<input type="checkbox"/>
42.5 (3 Dink)	<input checked="" type="checkbox"/>

Rear Hub Carrier	Alloy <input type="checkbox"/> Std <input checked="" type="checkbox"/>
Alloy Hub Carrier	+1° <input type="checkbox"/> -1° <input type="checkbox"/>

Rear - mm	Front - mm
Link Washers 2.0 mm	

Front Suspension	
Anti roll bar	No <input checked="" type="checkbox"/> 1.00 <input type="checkbox"/> 1.20 <input type="checkbox"/> 1.40 <input type="checkbox"/> 1.60 <input type="checkbox"/>

Camber at Ride Height	-0.5 Deg
Toe-In	+/- 0 Deg
Ride Height	20 mm
Washers	0 mm

Track Washers	1.0 mm
---------------	--------

33.5 (1 Dink)	<input type="checkbox"/>
38.0 (2 Dink)	<input type="checkbox"/>
42.5 (3 Dink)	<input checked="" type="checkbox"/>

Front Rake	10.0 Deg <input type="checkbox"/> 7.5 Deg <input checked="" type="checkbox"/>
------------	---

Link Washers	1.0 mm
Front Yoke	12.5 <input type="checkbox"/> (Kit) <input type="checkbox"/> 7.5 <input checked="" type="checkbox"/>