

Driver and Event	
Name	Lloyd Storey
Date	October 2012
Event	Stotfold winter series RD 1
Weather	Wet and cold
Result	TQ + 2nd

Track Conditions	
Surface	Astro
Grip Level	Low
Track Condition	Wet and slippery



Additional Settings	
Weights Added	See notes
Cell Layout	Forward
Ride Height	Front 21 mm Rear 23 mm
Washers between CTR and Bellcranks	0 mm
NOTES	Trish nose, servo & motor weight & 35g behind servo. Small bores. Forward cab. 4mm lwr tower wide ft and rear.

Electrics and Gearing	
E.S.C	SP Reventon Pro
Servo	Spektrum S6040
Receiver	Spektrum
Batteries	Thunder Power 5000 65C
Motor	SP 7.5
Spur	76
Pinion	24
Ext Gears	35/21 <input type="checkbox"/> 33/23 <input checked="" type="checkbox"/> 31/25 <input type="checkbox"/>

Wheels and Tyres	
Rear Wheels	Schumacher
Rear Tyre	Sch Silver minispikes
Rear Insert	Answer RC Blue
Front Wheels	Schumacher
Front Tyre	Sch silver low profile staggers
Front Insert	None

Differential Height	
High	<input type="checkbox"/>
Low	<input checked="" type="checkbox"/>

Rear Topdeck Link	
Turnbuckle	<input type="checkbox"/>
Moulding	<input checked="" type="checkbox"/>

Rear Shocks	
Oil	300 core
Spring	Silver Ass
Ball	Short <input type="checkbox"/>
Socket	Long <input checked="" type="checkbox"/>
Piston Holes	2 <input checked="" type="checkbox"/> 3 <input type="checkbox"/> 4 <input type="checkbox"/> 5 <input type="checkbox"/> 6 <input type="checkbox"/>
Shock Length Wound in all the way	

Front Shocks	
Oil	400 core, 1.3mm
Spring	Silver Kyosho
Piston Holes	2 <input checked="" type="checkbox"/> 3 <input type="checkbox"/> 4 <input type="checkbox"/> 5 <input type="checkbox"/> 6 <input type="checkbox"/>
Shock Length Wound in all the way	

Rear Suspension	
Anti roll bar	No <input checked="" type="checkbox"/> 1.20 <input type="checkbox"/> 1.40 <input type="checkbox"/> 1.60 <input type="checkbox"/>
Strap	3° <input type="checkbox"/> 4° <input type="checkbox"/> 5° <input type="checkbox"/>
Link Washers	0 mm
Antisquat Washers	1 mm
Link Washers	0 mm
Shock Postion	Front <input type="checkbox"/> Rear <input checked="" type="checkbox"/>
Wheelbase	Short <input checked="" type="checkbox"/> Med <input type="checkbox"/> Long <input type="checkbox"/>
Rear Camber at Ride Height	-1

Rear Hub Carrier	Alloy <input checked="" type="checkbox"/> Std <input type="checkbox"/>
Alloy Hub Carrier	+1° <input checked="" type="checkbox"/> -1° <input type="checkbox"/>
	49 <input checked="" type="checkbox"/> 44 <input type="checkbox"/> 39 <input type="checkbox"/> 34 <input type="checkbox"/>

Front Suspension	
Link Washers	0 mm
Yoke	0° <input type="checkbox"/> 5° <input checked="" type="checkbox"/>
Hub Carrier	High <input type="checkbox"/> Low <input checked="" type="checkbox"/>
Front Camber at Ride Height	-1
Front Toe In	0

Hub Carrier	High <input type="checkbox"/> Low <input checked="" type="checkbox"/>
	60.0 <input type="checkbox"/> 50.5 <input checked="" type="checkbox"/> 45.5 <input type="checkbox"/> 40.5 <input type="checkbox"/>