Driver Details	Notes
Name Jörn Neumann	SIGRMS
Date 4-6.09.20	
Event / Track EOS Round 2 Arena33	Shock oil front 550 and 450 rear. Front hex 3.0mm
Weather 20	Link washers front and rear 2mm.
Result TQ 1st	CTR washers 1mm
Chassis and Electrics	
Chassis Kit ☑ C/F □	Diff
Car Weight g Front Weight □ Rear weight □	Diff Height High ☑ Med ☐ Low ☐
Sidepods Kit ☑ C/F ☐ Alloy ☐	Diff Oil ™ cSt 2 Gear ☑ 4 Gear □
Front Hex	Diff Body Kit ☑ Alloy □
Bodyshell Storm lightweight	Ball Diff
ESC Maclan Racing Radio Tray Kit Brass	Motor and Gearing
Servo Highest D1000 Pro Under Servo Weight 🔽	Motor Maclan Racing 5.5T
Receiver Sanwa	Rotor Diameter 12.5 mm
LiPo Gens Ace 6000mAh Under LiPo Weight g	Timing 20 Deg Spur 83 Pinion 19
Track Conditions	Motor Plate Kit ☑ C/F □
Grip Level High ☐ Med ☑ Low ☐	Stock Layshaft Conversion
Type Tight ☐ Open ☑ Mixed ☐	Other Settings
Surface Clay ☐ Astro ☑ Grass ☐ Mixed ☐ Carpet ☐	LiPo Posts Forward □ Rearward ☑
Condition Smooth Bumpy D	LiPo Position Front ☐ Middle ☑ Rear ☐
Jumps Small ☐ Medium ☐ Large ☐ Mixed ☑	Front Wing Small Big
Wheels, Tyres and Inserts	Front Wing Gurney Height
Front Wheels Schumacher Rear Wheels Schumacher	Low Front Wing
Front Tyres Stagger Rear Tyres Minipin	Low Front Wing Gurney Height
Front Inserts Schumacher Rear Inserts Schumacher	Slipper 2 Plate ☐ 3 Plate ☑ 4 Plate ☐
Front Shocks Spring Shock Cap Sealed	Rear Shocks Spring Shock Cap Sealed □
Oil cSt Black Ib/in Vented ☐ Aeration ☑	Oil cSt Black Ib/in Vented ☐ Aeration ☑
Piston 3x1.5mm Hole Size mm Drilled	Piston 3x1.7mm Hole Size mm Drilled
Internal Limiters mm Kashima Body No□ Yes☑	
24,75 mm O`rings	34,90 mm O`rings
Front	
Toe 0 Deg Ride Height 18	nm 1.5 □ 1.6 ☑ 1.7 □ 1.6 ☑ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □
Yoke 0° □ 5° □ Alloy ☑ Camber at Ride He	
	□ -1.5 □ 0 □ +1.5 ☑
OTD 164 E Alley E	Link Washers mm
CTR Kit □ Alloy ☑	
Washers mm	Sall Stud Washer Shock Mount Kit □ C/F ☑
	Link Mount Kit ☑ Alloy□
Hub Carrier Kit □ Alloy ☑	
Hub Height High ☐ Middle ☑ Low ☐	
Rear	
Anti Roll Bar None 🗹	
FR Strap Kit ☑ Brass ☐ Ride Height 18 RR Strap Kit ☑ Brass ☐ Camber at Ride Height	mm
RR Strap Kit Brass Wheelbase Short	t 1.5 Deg ☑ ☑ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐
Wileelbase Officit	
	□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
	Shock Position
Hub Washers mm	Rearward D Forward D
Toe in 4° \(\text{3.5}\) 3° \(\text{Z} \) 2.5° \(\text{L} \)	
2° \(\tau \) 1.5° \(\tau \) 1° \(\tau \) 0.5° \(\tau \)	
Anti-squat 1° □ 2° ☑ 3° □ 4° □	
Rear Pin High (kit) 🔽 Low 🗆	Link Washers mm
Hub Carrier Kit ☑ Alloy □	
Brass Insert Hi-pin □ Low-pin □	Link Mount Kit □ Alloy ☑