



Track Conditions	☐ Indoor	☐ Outdoor	☐ Low	☐ Medium	☐ High	☐ _____	☐ Astroturf	☐ Blue Groove	☐ Hard Packed	☐ Clay
	☐ Bumpy	☐ Smooth	☐ Open	☐ Medium	☐ Tight	☐ _____	☐ Carpet	☐ Dirt	☐ _____	

Rear Suspension

Camber: _____

Ride Height: _____

Sway Bar: _____

Toe-in: _____

Anti-Squat: _____

Shims

☐ + ☐ 0°

☐ - ☐ 0.5°

☐ 1.0°

☐ 1.5°

☐ 2.0°

Outboard Toe

☐ + ☐ 0°

☐ - ☐ 0.5°

☐ 1.0°

☐ 1.5°

☐ 2.0°

Rear Bulkhead Weight

☐ Yes

☐ No

Upright

☐ Stock ☐ Aluminum

Hex Spacer

☐ +0.75mm

☐ 0mm

☐ -0.75mm

RR-FR Toe Block

☐ Stock ☐ Brass

Shims

☐ 0R ☐ 0 ☐ 0L ☐ Up ☐ 0R ☐ 0 ☐ 0L

☐ 1R ☐ 1 ☐ 1L ☐ Down ☐ 1R ☐ 1 ☐ 1L

☐ 2R ☐ 2 ☐ 2L ☐ 2R ☐ 2 ☐ 2L

Shims

☐ 0R ☐ 0 ☐ 0L ☐ Up ☐ 0R ☐ 0 ☐ 0L

☐ 1R ☐ 1 ☐ 1L ☐ Down ☐ 1R ☐ 1 ☐ 1L

☐ 2R ☐ 2 ☐ 2L ☐ 2R ☐ 2 ☐ 2L

Shocks	Front		Rear	
Piston (1)				
Oil				
Spring				
Limiters (2)				
Length (3)				
Rebound				
Bladder/Seal (4)				
Spring Bucket				



Battery & Weight

Battery Position: ☐ Forward ☐ Middle ☐ Aft ☐ _____

Measured from inside Front cross brace



Battery Type
☐ Standard
☐ Shorty

Car Weight: _____

Bias - Front: _____ Rear: _____

Differential	Diff Height ☐ Low ☐ Medium ☐ High ☐ Ball Differential	Electronics	Motor: _____	Radio: _____	Body & Wings	Body: _____
	☐ Gear Differential Oil: _____		Timing: _____	Receiver: _____		Wing: _____
			Spur: _____	Servo: _____		Angle: _____
			Pinion: _____	ESC: _____		Width: _____
			Internal Ratio: 2.43	_____		Lip: _____
			Final Ratio: _____	Battery: _____		Front Wing: _____

Tires	Tire Information		Comments
	Front	Rear	
Brand/Model			
Compound			
Insert			
Wheel			
Additive			
Comments			