

SPYDER SRX2

Mid-Motor Set-up Sheet

Driver:
Jared Kirkwood
Date:
02-01-14
Track-Temp
55
Air-Temp
65

Event:
WRL 3.4
Track:
The Loft RC Raceway
Country/City/State:
Columbus, OH, USA

| Track Conditions | <input checked="" type="checkbox"/> Indoor | <input checked="" type="checkbox"/> Tight | <input type="checkbox"/> Medium | <input checked="" type="checkbox"/> Smooth | <input checked="" type="checkbox"/> Hard Packed | <input type="checkbox"/> Grass | <input type="checkbox"/> Astro-turf | <input checked="" type="checkbox"/> Clay | <input checked="" type="checkbox"/> Low Bite | <input type="checkbox"/> High Bite | |
|-------------------------|---|---|---|---|--|---|---|--|--|--|--|
| | <input type="checkbox"/> Outdoor | <input type="checkbox"/> Open | <input type="checkbox"/> _____ | <input type="checkbox"/> Rough | <input type="checkbox"/> Blue Groove | <input type="checkbox"/> Carpet | <input type="checkbox"/> Multi-Surface | <input checked="" type="checkbox"/> Moist | <input type="checkbox"/> Med Bite | <input checked="" type="checkbox"/> Low-Medium | |
| Front Suspension | Sway Bar: | <input type="checkbox"/> Yes | Size _____ mm | Caster Block Inserts | | | Bump Steer | Steering Ackerman | | | |
| | <input checked="" type="checkbox"/> No | <input checked="" type="checkbox"/> + 0 Deg | | | <input checked="" type="checkbox"/> 2.5 Deg | <input type="checkbox"/> 5 Deg | <input checked="" type="checkbox"/> Shims 0 mm | <input type="checkbox"/> Opt.1 | <input checked="" type="checkbox"/> Opt.2 | <input type="checkbox"/> Opt.3 | |
| | Ride Height: | 23 | mm | | | | | | | | |
| | Camber: | 1 | deg | | | | | | | | |
| | Toe: | <input type="checkbox"/> In | <input checked="" type="checkbox"/> Out .5 | ° | Shims mm | Spindle Shims | | <input checked="" type="checkbox"/> Shims 1 mm | | | |
| Front Bulkhead | Insert | | <input type="checkbox"/> 20° | <input checked="" type="checkbox"/> 25° | <input type="checkbox"/> 30° | | | | | | |
| | | | <input checked="" type="checkbox"/> Stock / 25° | <input type="checkbox"/> Brass | <input type="checkbox"/> Aluminum | | | | | | |
| | | | | | | | | | | | |
| Rear Suspension | Sway Bar: | <input type="checkbox"/> Yes | Size _____ mm | Outboard Toe-in | | | Rear of Buggy | Wing Mount | | | |
| | <input checked="" type="checkbox"/> No | <input checked="" type="checkbox"/> + 0.5 deg | | | <input type="checkbox"/> 1.0 deg | <input type="checkbox"/> 1.5 deg | <input type="checkbox"/> 2.0 deg | <input checked="" type="checkbox"/> Std. | <input type="checkbox"/> Low | | |
| | Ride Height: | 24 | mm | <input checked="" type="checkbox"/> Shims mm | | | | | | | |
| | Camber: | 1.5 | deg | <input type="checkbox"/> C | <input type="checkbox"/> B | <input type="checkbox"/> A | | | | | |
| | RR-FR-Toe-Block | <input checked="" type="checkbox"/> Stock | <input type="checkbox"/> Brass | <input type="checkbox"/> D | <input type="checkbox"/> E | | | | | | |
| | <input type="checkbox"/> OR <input checked="" type="checkbox"/> 0 <input type="checkbox"/> 0L <input type="checkbox"/> UP <input type="checkbox"/> 0R <input type="checkbox"/> 0 <input checked="" type="checkbox"/> 0L | <input type="checkbox"/> 1R <input type="checkbox"/> 1 <input type="checkbox"/> 1L <input type="checkbox"/> Down <input type="checkbox"/> 1R <input type="checkbox"/> 1 <input type="checkbox"/> 1L | <input type="checkbox"/> 2R <input type="checkbox"/> 2 <input type="checkbox"/> 2L <input type="checkbox"/> 2R <input type="checkbox"/> 2 <input type="checkbox"/> 2L | | | | | | | | |
| | <input type="checkbox"/> OR <input checked="" type="checkbox"/> 0 <input type="checkbox"/> 0L <input type="checkbox"/> UP <input type="checkbox"/> 0R <input type="checkbox"/> 0 <input checked="" type="checkbox"/> 0L | <input type="checkbox"/> 1R <input type="checkbox"/> 1 <input type="checkbox"/> 1L <input type="checkbox"/> Down <input type="checkbox"/> 1R <input type="checkbox"/> 1 <input type="checkbox"/> 1L | <input type="checkbox"/> 2R <input type="checkbox"/> 2 <input type="checkbox"/> 2L <input type="checkbox"/> 2R <input type="checkbox"/> 2 <input type="checkbox"/> 2L | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| Shocks | Front Shock Piston (1): | 1.6 mm X 2 | Rear Shock Piston (1): | 1.7 mm X 2 | | | | Battery Location (Measured from inside Front cross brace): | | | |
| | Shock Brand/Oil : | 325cst | Shock Spring : | Kyo Pink | Tamiya Red | <input type="checkbox"/> Weight Placement | Type the weight in grams at the location it's placed on the chassis | Distance | 0 mm | | |
| | Shock Limiters(2): | 3 mm | Shock Length (3): | 86.75 mm | 101.5 mm | <input type="checkbox"/> (5) | | | | | |
| | Rebound (4): | 0 mm | Bladder / Seal (5): | seal | seal | <input type="checkbox"/> (1) | | | | | |
| | Spring Bucket : | high | | | | <input type="checkbox"/> (2) | | | | | |
| | | | | | | <input type="checkbox"/> (3) | | | | | |
| | | | | | | <input type="checkbox"/> (4) | | | | | |
| | | | | | | <input type="checkbox"/> (5) | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| Gearing | Spur Gear (A): | 78 T | Differential | Diff Height | Electrics | Body : | Serpent | | | | |
| | Pinion Gear (B): | 23 T | | <input checked="" type="checkbox"/> High | Radio : M12 | Wing Rear: | Serpent | | | | |
| | Gear Ratio (A/B)=C: | 3.391 | | <input type="checkbox"/> Med | ESC : SP Revonton Pro | Wing Width: | 166 mm | | | | |
| | Final Drive (C*2.43): | 8.241 | | <input type="checkbox"/> Low | Motor : Reedy 8.5 w/12.2 | Wing Lip : | 17 mm | | | | |
| | | | | <input checked="" type="checkbox"/> Ball Differential | Servo : KO RSx One10 | Wing Angle : | 2 | | | | |
| | | | <input type="checkbox"/> Gear Differential | Battery : Reedy 5800 #314 | Wing Front: | -- | | | | | |
| Tires | Brand: | Front AKA | Rear AKA | Comments | Indoor but cold. Rear wing mounted 13mm back. | | | | | | |
| | Model Name: | Typo | Typo | | Brass plate under battery towards back of tray (20g). | | | | | | |
| | Compound: | Clay | Clay | | Machined pistons (Rocket RC Parts). | | | | | | |
| | Insert Type: | EVO Red | EVO Red | | EXPO: -15%S/-10%T ESC: lvl3, 14%DB, 47%B | | | | | | |
| | Wheels: | EVO | EVO | | Consider wide rear hexes, 350cst oil, 1 or 1.5mm rear camber link shims, and middle height on spindle. | | | | | | |
| Tire Additive: | MoGrip | MoGrip | | | | | | | | | |