

Name: SWORKz
 Date: 2025
 Track: Carpet

Diff. Oil

Rear: _____
 10000

Diff. Type

☒ Gear Diff
☐ Ball Diff

Track Conditions

Size: ☐ Open ☒ Med. ☐ Tight
 Traction: ☒ High ☐ Med. ☐ Low ☐ Wet
 Surface: ☒ Smooth ☐ Med. ☐ Bumpy

Tire

Front
 Type: Option (JC)
 Foam: Option

Rear
 Type: Option (JC)
 Foam: Option

Electric System

ESC Type: Option (XERUN XR10 Pro-Black-G3)
 Motor Type: Option (XERUN V10-7.5T G3)
 Motor Gear/Spur Gear: 21/81 T
 Battery Type: Option (T-Pro 4800 mAh LCG)

Front Suspension

1 2 3 4 5
☐ ☐ ☐ ☐ ☒

0 mm

Camber: _____ mm (-1°)

Upper (1.5) mm
 Lower (3.2) mm

1 2 3 1 2 3

Toe Angle: _____ mm (1°)

0 2.5 -2.5 5 -5

1
☒ 2
☒ 4.7mm
☒ 5.7mm
☒ 6.7mm
☒ 7.7mm

Front Lower Arm Holder
☒ +2.5 ☐ -2.5

☒ Standard
☐ 25g Brass

Front Sway bar ☒ Use 1.2 mm
☐ None

Front Lower Arm Holder
 Adjustment ☒ 0.5mm ☐ 1mm

Diff. Position

Ride High: _____ 14 mm

Oil: _____ #500
 Spacer: _____ 2 mm
 Pistons: 2Hx1.7mm
 Spring: _____ 5-Dot

22 mm

Rear Suspension

1 2 3 4 5
☐ ☐ ☐ ☐ ☒

2 mm

Camber: _____ mm (1.5°)

4.7mm
☒ 5.7mm
☒ 6.7mm
☒ 7.7mm

1 ☒ 2 ☒ 3

1 ☒ 2 ☒ 3

Rear Toe-In

F
☐ 0.5 ☒ 1.0

R
☐ 0.5 ☒ 1.0

Wing Angle ☒ 0 ☐ +3 ☐ -3

Wing Position

Body: SWORKz Kit
 Rear Wing: SWORKz Kit
 Front Wing: SWORKz Kit

Notes: Battery position forward
 Front: 222009(M)
 222010(S)
 Rear: 222009(H)
 222010(M)

Rear Sway bar ☒ Use 1.4 mm
☐ None

Ride High: _____ 15 mm

Oil: _____ #500
 Spacer: _____ 0 mm
 Pistons: 2Hx1.8mm
 Spring: _____ 4-Dot

28 mm

Option Parts List

Front lower arm
☐ Carbon composite Hard Material ☒ Standard Material

Rear lower arm
☐ Carbon composite Hard Material ☒ Standard Material

Side guard
☒ Standard Material