

S3XE.1

new generation rc car

**1/8 OFF-ROAD 4WD ELECTRIC
RC PROFESSIONAL BUGGY**



INSTRUCTION MANUAL



PROFESSIONAL RC CAR

www.wrc-racing.com



INTRODUCTION

SBXE is a new generation high quality 1/8 scale electric off-road buggy.
SBXE is supplied in a box, you can download the Instruction manual from www.wrc-racing.com
Its use is intended for more than 16 years old persons with experience on rc model car field.
Children and all the persons without this requirement MUST have direct supervision of a knowledgeable adult responsible.

SAFETY PRECAUTIONS

Instruction Manual MUST be read and fully understood before to start building and operating functions.
Always keep Instruction Manual in safety place, ready to be consulted for any reference you need.
Use only original WRC spare parts.

GENERAL INFORMATION

Assemble the kit only away from the reach of children.
Follow the building and operating instructions using the utmost care.
Don't put any part of your body inside rotating and moving elements as this may cause damage or serious injury.
Check and clean the model before putting it away.
Don't use your model car in public places or in roads and areas where it could generate conflict with person or vehicular traffic.
The model car is controlled by radio: you MUST put great care to avoid loss of radio control always keeping a safety margin all around your model in order to prevent any collision.
Operating frequency: check and be sure it is clear and not shared with anybody at same time; it could cause loss of control of the RC model.
Always turn on your transmitter before you turn on the receiver in the car and always turn off the receiver before you turn off your transmitter.
Keep the wheels of the model off the ground when checking the operation of the radio equipment.
Disconnect the battery pack before storing your model.

WARRANTY

WRC guarantees this model kit to be free from defects in both material and workmanship within 30 days of purchase.
The total monetary value under warranty will in no case exceed the cost of the original kit purchased.
This warranty doesn't cover any components damaged by use or modification or as result of wear.
Part or parts missing from this kit must be reported within 30 days of purchase.
No part or parts will be sent under warranty without proof of purchase.
If you find a defective or missing part, contact the local distributor.
Customer service and support will be provided through local hobby store.
No warranties are expressed or implied that cover damage caused by what is considered normal use or cover or imply how long any model cars' components or electric components will last before requiring replacement.
Due to the high performance level of this model car you will need to periodically maintain and replace consumable components; any and all warranty coverage will not cover replacement of any part or component damaged by neglect, abuse or improper or unreasonable use.
This includes but is not limited to damage from crashing, excessive moisture, improper use or no maintenance or user modifications which compromise the integrity of components.
Warranty will not cover components that are considered consumable on RC model car.
WRC doesn't pay nor refund on any component sent from WRC or its distributor for warranty.
WRC reserves the right to make final determination of the warranty status of any component or part.
Use only original WRC spare part:

CUSTOMER SUPPORT

Please don't hesitate to contact WRC support at info@wrc-racing.com for any problem or question.
Also kindly visit our website www.wrc-racing.com to find last updates, set-up information, option parts and other information.

W.R.C. world racing car s.r.l.

Via Meucci, 23/B
36040 Brendola (VI)
ITALY

Phone: 0039 0 444 401138
fax: 0039 0 444 401139
E-mail: info@wrc-racing.com
Website: www.wrc-racing.com



PROFESSIONAL RC CAR



TECHNICAL INFORMATION

- WHEELS LOCK:Lightweight 17 mm 7075 T6 Nut
- CHASSIS:3.0 mm Swiss 7075 T6 aluminium
- RADIO PLATE:Composite Material
- DRIVETRAIN TYPE:Spring steel CVD Driveshfts
- FRONT DIFFERENTIAL:Differential Gear
- REAR DIFFERENTIAL:Differential Gear
- SUSPENSION:Pivot ball suspension
- RIDE HEIGHT:Adjustable Front & Rear
- CAMBER:Adjustable Front & Rear
- CASTER:Adjustable Front
- TOE:Adjustable Front & Rear
- ROLLCENTER:Adjustable Front & Rear
- ACKERMANN:Adjustable Front
- ANTI-ROLL BARS:Adjustable Front & Rear

TECHNICAL DATA

- WIDTH310 mm
- WHEEL BASEadjustable 315-320 mm.

ADDITIONAL ITEMS NEEDED FOR COMPLETION (REQUIRED BUT NOT INCLUDED IN THE KIT)



ELECTRIC MOTOR




TRANSMITTER




RECEIVER



LOW PROFILE STEERING SERVO




AA ALKALINE BATTERIES
FOR TRANSMITTER
AND RECEIVER




WHEEL - TYRES - INSERTS

2 X 7.4 V



1 X 14.8 V




OR


LIPO BATTERIES

TOOLS REQUIRED

THESE TOOLS ARE NOT INCLUDED IN THE KIT BUT ARE REQUIRED FOR PROPER ASSEMBLY




ALLEN:
1.5 MM.
2.0 MM.
2.5 MM.
3.0 MM.



RING PLIERS




SIDE CUTTER





SCISSORS



NOTICE:



THE FOLLOWING ITEMS ARE NEEDED FOR COMPLETION OF THE SBXE; THEY ARE NOT INCLUDED IN THIS KIT (UNLESS NOTED) AND SHOULD BE OBTAINED FROM YOUR LOCAL HOBBY SHOP.
BE SURE TO READ THE INSTRUCTION COMPLETELY PRIOR TO ASSEMBLY



















SCREW POSITION





BAG 7





Front Upright






























Assembly 2 set



SHOCK FILLING

Fully extend the piston rod so the piston is at the bottom of the shock body.



Hold the shock upright and fill the shock body with shock oil as in the picture.


Let the oil settle and allow air bubbles to rise to the top. Slowly move the piston up and down until no more air bubbles appear. Add shock oil as necessary.

Pull the piston rod most of the way out of the shock bod. Let the shock rest for 5 minutes to allow the air bubbles to scape.


P- ONE SHOCKS OIL	
CODE	CST
SO-400	400
SO-500	500
SO-600	600 (IN KIT)
SO-700	700
SO-800	800

Set distance





Assembly 2 set



SHOCK FILLING



Fully extend the piston rod so the piston is at the bottom of the shock body.


Hold the shock upright and fill the shock body with shock oil as in the picture.

Let the oil settle and allow air bubbles to rise to the top. Slowly move the piston up and down until no more air bubbles appear. Add shock oil as necessary.

Pull the piston rod most of the way out of the shock bod. Let the shock rest for 5 minutes to allow the air bubbles to scape.


P- ONE SHOCKS OIL	
CODE	CST
SO-400	400
SO-500	500
SO-600	600 (IN KIT)
SO-700	700
SO-800	800







Tires

Assembly 4 set





Body





Driver: _____
Date: _____


Track: _____
Event: _____

Front Suspension:

Ride Height:
Camber:
Toe:
Anti-Roll Bar
Size:
Gap:
Ackerman
1
2
3
4
Drive Shaft:
Chassie Brace:
Hex:




Caster Shim:



Upper Ball Type:

Caster Shim:

Upper Ball Shim:




Washer:

1 2

Lower Ball Shim:


Wheelbase Shim:




Lower Ball Type:

Wheelbase Shim:

Lower Arm Position




Upper Arm Position




Rear Suspension:

Ride Height:
Camber:
Toe:
Anti-Roll Bar
Size:
Gap:
Drive Shaft:
Chassie Brace:
Hex:




Hub Shim:



Wheelbase Shim:


Shim:

Lower Arm Position



Shocks:

	Front	Rear
Piston:		
Membrane:		
Oil:		
Spring:		
Rebound:		
Free Length:		



Differential:

	Front	Center	Rear
Case Mat.:			
Oil:			
Crown Gear:			
Gearing :			
Spur Gear:		Pinion:	
Notes:			

Tires:

	Front	Rear
Brand:		
Compound:		
Insert:		
Whells:		
Weight:		
Total Vehicle Weight:		

Tracks:

Size :
Traction:
Surface:
Type:
Condition:
Temperature:

Body, Wing:

Body:
Wing:
Wing Height:
Gap to tower:

Electronics:

Radio :			
Servo:			
Epa:	Throttle:	% Brake:	%
Expo:	Throttle:	% Brake:	%
Esc:			
Motor:			
Battery:			



W.R.C. world racing car s.r.l.

Via Meucci, 23/B 36040 Brendola (VI) - ITALY - commerciale@wrc-racing.com

www.wrc-racing.com