

X - 5 SET-UP

Date: 30 / 09 / 07

Track: workshop indoors

FRONT

Camber + -- -0.5

Toe ☐ In ☐ Out 0

Bones ☒ Below ☐ Level ☐ Above

Sway Bar ☒ No ☐ Yes

Steering Bellcrank # Washers 0

Ackerman ☐ Inside ☒ Outside

REAR

Camber + -- -1

Toe In Pivot 3 HubCar. 0

Bones ☐ Below ☒ Level ☐ Above

Antisquat 1

Hub Spacing ☐ Rr ☒ Center ☐ Frt

Sway Bar ☒ No ☐ Yes

SHOCKS Oil 37.5

Piston 556 ☐ Std. ☒ Drilled

Shaft Length Overall std

Limiters Inside 0 Out 0

Spring green

Mounting (T / B) 2 / 1
1=inside

SHOCKS Oil 25

Piston red ☒ Std. ☐ Drilled

Shaft Length Overall std

Limiters Inside 0 Out 0

Spring red

Mounting (T / B) 2 / 2
1=inside

CAMBER LINK Inner Mount 2
1=inside

washers 1

CAMBER LINK Inner Mount 1b
1=inside T=Top M=Middle B=Bottom

Outer Mount 3
1=inside

DIFF ☒ 1-way ☐ Diffs

Driveshafts ☒ CVDs ☐ Bones

☐ Alum ☒ Steel

Outdrives ☐ Plastic ☒ Steel

DIFF Driveshafts ☐ CVDs ☒ Bones

☐ Alum ☒ Steel

Outdrives ☒ Plastic ☐ Steel

BELT DRIVE Drive Gear

Diff Gears

MOTOR Type 5.5

Wind

PINION/SPUR 14/106

Pinion ☒ Steel ☐ Alum

TIRES Front schuy Rear mini pin

Wear schuy minipin
1=New 5=Bald

CHASSIS ☐ Delrin ☐ Alum ☒ Graph