X - 5 SET-UP

Date: 😉	113100	Track: Albuquerque
FRONT		med illats REAR
Camber	+ 连	Camber + 🕒
Toe ☑ In	Out <u>leach</u> side	Toe In Pivot HubCar
Bones Below Level Above		Bones ☐ Below ☐ Level ☐ Above
Sway Bar 🔼 No 🗌 Yes		Antisquat 10 Shims
Steering Bellcrank # Washers		Hub Spacing ☐ Rr ☑ Cemter ☐ Frt
Ackerman ☑ Inside ☐ Outside		Sway Bar
SHOCKS Oil 30		shocks oil 35
Piston 5		Piston Std. Drilled
Shaft Length Overall 1,176		Shaft Length Overall
Limiters Inside 90 Out 200135		Limiters Inside 60 Out 0
Spring <u>Creen</u>		Spring <u>Cink</u>
Mounting (T / B) /		Mounting (T / B) 2 / 1=inside
CAMBER LINK Inner Mount		CAMBER LINK Inner Mount 1=inside T=Top M=Middle B=Bottom
# washers	<u> </u>	Outer Mount1=inside
DIFF	☑ 1-way ☐ Diffs	<u>DIFF</u> Driveshafts ⊠CVDs ☐ Bones
Driveshafts	☑ CVDs ☐ Bones	DAlum ☐ Steel
		Outdrives Plastic Steel
Outdrives	☑ Plastic ☐ Steel	BELT DRIVE Drive Gear
		Diff Gears 28
MOTOR Type	D-5	TIRES Front Red Topers R-3 Blue Blue white
Wind	10× 10 1	TIRES Front Red Topers R-3 Buil Twins Rear Trinity Blue. Wear 3.5 1=New 5=Bald
PINION/SPUR	16/102	<u>CHASSIS</u> ☐ Delrin ☐ Alum ☑ Graph
Pinion		wing washers 2