

X-60 Setup Sheet

Driver:				Date:						
Track / Location:				Event:						
Tight ☐	Both ☐	Open ☐	Wet ☐	Damp ☐	Dry ☐	Smooth ☐	Rough ☐	Slippery ☐	Medium ☐	High-Bite ☐

FRONT**SUSPENSION**

Ride Height: _____

Camber: _____ Toe: _____

Camber Link: Inside: _____ Washers: _____ Outside: _____
1=inside A=inside

Caster Block: _____

Bump steer spacers: ☐ 0.050" (Stock)/ ☐ OTHER: _____

Spacers under outer tie-rod ballstud: _____

Axle: _____

Axle height: _____

Steering Ackerman: _____

Servo Position: _____

SHOCKS

Brand: _____

Top Mounting: _____

Bottom Mounting: _____

Spring: _____

Piston: _____
☐ Standard/ ☐ Drilled

Oil: _____

Top Limiting: _____

Bottom Limiting: _____

Arn0 at petitrc.com

REAR**SUSPENSION**

Ride Height: _____

Transmission: _____

Transmission Height: ☐ .060 (Stock) / ☐ Other: _____

Camber: _____ Toe Bar: _____ Anti-squat: _____

Extra Hub Toe In/Out: _____

Rear Roll Bar: _____

Camber Link: Inside: _____ Washers: _____ Outside: _____
1=inside A=inside

Hub spacing: _____

Arm spacing: _____

SHOCKS

Brand: _____

Top Mounting: _____

Bottom Mounting: _____

Spring: _____

Piston: _____
☐ Standard/ ☐ Drilled

Oil: _____

Top Limiting: _____

Bottom Limiting: _____

OTHER

Front tires:	Front inserts:
Rear tires:	Rear inserts:
Esc:	Motor:
Battery:	Pinion/spur: ____/____
Wing:	Front Wing: