$X - 6^2$ Set-Up Sheet				
Driver: Dan Griffin			Date: 3-1-2009	
Track: Clay Track Lower Bite Set Up				
Tight/Open 1=very tight 5=very open	Wet/Dry 1=very wet 5=very dry	Smooth/F 1=very smooth 5=		Slippery/High-Bite 1=very slick 5=very high bite
Front				
Suspension			Shocks	
Ride Height: <u>Arms Level</u>			Losi Associated	
Camber: $\underline{-1}^{\circ}$ Toe In/Out: $\underline{\text{In}}$ $\underline{1}^{\circ}$			Oil Make: <u>Associated</u>	
Camber Link: Inside: $\underline{1}_{\text{l=inside}}$ Washers: $\underline{0}$ Outside: $\underline{A}_{\text{A=inside}}$			Mounting (Top/Bottom):2/2	
Caster Block (20°/25°/30°): <u>30</u> °				Spring: Orange
Castor Block Position (Forward/Back): Forward			Piston: <u>55(orange)</u> Std/Drilled <u>Standard</u>	
Bump Steer Spacers 0.05" (Stock 2)/Other: 2			Oil: 35wt AE	
Spacers under inner Tie-Rod Ballstud: <u>0</u>			Limiting (In/Out): <u>.090"/</u>	
Axle Type (Trailing/Inline) : <u>Trailing (stock)</u>				
Axle Height Top/Middle/Bottom: <u>Bottom</u>				
Steering Ackerman: <u>Forward (stock)</u> Servo Position: <u>Forward</u>				
Rear				
Suspension			Shocks	
Transmission Height (Multiples of 0.03"): <u>.06</u>			Losi ⊠/Associated □	
Ride Height: <u>CVD's above level</u>			Oil Make: <u>Associated</u>	
Camber: -1° Toe Bar 3°/4°: 4° Antisquat: 1 small washer Extra Hub Toe In/Out: No/			Mounting (Top/Bottom): $1/2$ $1=inside$	
Rear Roll Bar: No Size:			Spring: Pink	
_			Piston: <u>56(red)</u> Std/Drilled <u>Standard</u>	
Camber Link: Inside: $\underline{\underline{I}}$ Outside: $\underline{\underline{B}}$ A=inside			Oil: <u>30 wt AE</u>	
Washers Under Inner Ballstud: 0			Limiting (In/Out): <u>0.120"/0</u>	
Hub Spacing: <u>Forward</u> Arm Spacing: <u>Forward</u>				
Other				
Notes: 1oz / 28 grams of weight up front around the bulkhead				
Front Tire: Pink 2wd front tapers				
Rear Tire: Pink BK Bars, Trinity Bomb1 foam				
Motor: 7.5 Pinion/Spur: 23				
Rear Wing: X - 6 wing with very small gurney, forward and low Front Wing: Yes				