2WDRC.com 4WDRC.com	X-6 ²	Setup	Sheet	•		TORY R/C pryRC.com
Driver:		-		Date:		•
Track / Location:				Event:		
	amp Dry	Smooth	Rough			High-Bite
		FRONT				
SUSPENSION			SHOCKS			
Ride Height:				Brand:		<u> </u>
Camber: Toe:				Top Mounting: Bottom Mounting: Spring: Piston:		
Camber Link: Inside: Washers: Outside: A=inside						
Caster Block:						
				□ Sta	ndard/ 🛭	Drilled
Bump steer spacers: □ 0.050" (Stock)/ □ OTHER: Spacers under outer tie-rod ballstud:				Oil:		
Axle:				Top Limiting: Bottom Limiting:		
Axle height:						
Steering Ackerman:						
Servo Position:					Arr	n0 at petitrc.com
		REAR				
SU	SPENSION				SHOCKS	3
00	O				000	
Ride Height:				Brand:		
				Top Mountin	ng:	
Ride Height:			_	Top Mountin Bottom Mou	ng: ınting:	
Ride Height: Transmission: Transmission Height: □.060 (St Camber: Toe Bar:	ock) / 🗆 Othe	er:		Top Mounting Bottom Mou	ng: unting:	
Ride Height: Transmission: Transmission Height: □.060 (St Camber: Extra Hub Toe In/Out:	ock) / 🗆 Othe	er:		Top Mounting Bottom Mou Spring:Piston:	ng: unting:	
Ride Height: Transmission: Transmission Height: □.060 (St Camber: Extra Hub Toe In/Out: Rear Roll Bar:	ock) / 🗆 Othe	er: Anti-squat:_		Top Mounting Bottom Mou Spring:Piston:	ng: unting: ndard/	Drilled
Ride Height: Transmission: Transmission Height: □.060 (St. Camber: Extra Hub Toe In/Out: Rear Roll Bar: Camber Link: Inside: 1=inside	ock) / 🗆 Othe	er: Anti-squat:_ Outside:_		Top Mounting Bottom Mou Spring: Piston:	ng: unting: ndard/ c	Drilled
Ride Height: Transmission: Transmission Height: □.060 (St. Camber: Extra Hub Toe In/Out: Rear Roll Bar: Camber Link: Inside:	ock) / 🗆 Othe	er: Anti-squat:_ Outside:_		Top Mounting Bottom Mou Spring: Piston:	ng: unting: ndard/ c	Drilled
Ride Height: Transmission: Transmission Height: □.060 (St Camber: Extra Hub Toe In/Out: Rear Roll Bar: Camber Link: Inside: 1=inside Hub spacing:	ock) / 🗆 Othe	er: Anti-squat:_ Outside:_		Top Mounting Bottom Mou Spring: Piston:	ng: unting: ndard/ c	Drilled
Ride Height: Transmission: Transmission Height: □.060 (St Camber: Extra Hub Toe In/Out: Rear Roll Bar: Camber Link: Inside: 1=inside Hub spacing:	ock) / 🗆 Othe	er: Anti-squat:_ Outside:_ A=		Top Mounting Bottom Mou Spring: Piston:	ng: unting: ndard/ c	Drilled
Ride Height: Transmission: Transmission Height: □.060 (St Camber: Extra Hub Toe In/Out: Rear Roll Bar: Camber Link: Inside: 1=inside Hub spacing:	ock) / 🗆 Othe	er: Anti-squat:_ Outside:_ A=		Top Mounting Bottom Mou Spring: Piston:	ng: unting: ndard/ c	Drilled
Ride Height: Transmission: Transmission Height: □.060 (St Camber: Extra Hub Toe In/Out: Rear Roll Bar: Camber Link: Inside: 1=inside Hub spacing:	ock) / 🗆 Othe	er: Anti-squat:_ Outside:_ A=		Top Mounting Bottom Mou Spring: Piston:	ng: unting: ndard/ c	Drilled
Ride Height: Transmission: Transmission Height: □.060 (St Camber: Extra Hub Toe In/Out: Rear Roll Bar: Camber Link: Inside: 1=inside Hub spacing:	ock) / 🗆 Othe	er: Anti-squat:_ Outside:_ A=		Top Mounting Bottom Mou Spring: Piston:	ng: unting: ndard/ c	Drilled
Ride Height: Transmission: Transmission Height: □.060 (St Camber: Extra Hub Toe In/Out: Rear Roll Bar: Camber Link: Inside: 1=inside Hub spacing:	ock) / 🗆 Othe	er: Anti-squat:_ Outside:_ A=		Top Mounting Bottom Mou Spring: Piston:	ng: unting: ndard/ c	Drilled
Ride Height: Transmission: Transmission Height: □.060 (St Camber: Extra Hub Toe In/Out: Rear Roll Bar: Camber Link: Inside: 1=inside Hub spacing:	ock) / 🗆 Othe	er: Anti-squat:_ Outside:_ A=		Top Mounting Bottom Mou Spring: Piston:	ng: unting: ndard/ c	Drilled
Ride Height: Transmission: Transmission Height: □.060 (St Camber: Extra Hub Toe In/Out: Rear Roll Bar: Camber Link: Inside: 1=inside Hub spacing:	ock) / 🗆 Othe	Anti-squat: Outside: A= OTHER	inside	Top Mounting Bottom Mou Spring: Piston:	ng: unting: ndard/ c	Drilled
Ride Height: Transmission: Transmission Height: □.060 (St Camber: Extra Hub Toe In/Out: Rear Roll Bar: Camber Link: Inside: 1=inside Hub spacing: Arm spacing: Front tires: Rear tires:	ock) / 🗆 Othe	Anti-squat: Outside: A= OTHER From Rear	inside t inserts: inserts:	Top Mounting Bottom Mou Spring: Piston:	ng: unting: ndard/ c	Drilled
Ride Height: Transmission: Transmission Height: □.060 (St Camber: Extra Hub Toe In/Out: Rear Roll Bar: Camber Link: Inside: 1=inside Hub spacing: Arm spacing: Front tires:	ock) / 🗆 Othe	Anti-squat:_ Outside:_ A= OTHER From Rear Moto	inside t inserts: inserts:	Top Mounting Bottom Mou Spring: Piston:	ng: unting: ndard/ c	Drilled