

RACE
 TRACK
 NAME DATE

LAPS BEST LAP TIME sec
 QUALIFYING POSITION FINAL POSITION

TRACK

SIZE OPEN MEDIUM TIGHT

TRACTION VERY-LOW MEDIUM VERY-HIGH

SURFACE SMOOTH MEDIUM BUMPY

TYPE CLAY CARPET ASTRO

CONDITION BLUE GROOVE HARD PACKED DRY
 DUSTY LOAMY WET

TRANSMISSION

BALL DIFF GEAR DIFF ACTIVE DIFF

DIFFERENTIAL OIL cst 60° 90° 120°

SATELLITE GEARS COMPOSITE STEEL GEARS 2 4

SLIPPER mm SOLID AXLE

2-PAD SLIPPER CLUTCH PLATES SLIPPER PADS

VENTILATED STANDARD KIT

GEARING

PINION SPUR GEAR

TYPE 3G 5G REAR LCG KIT GRAPHITE

FRONT SHOCKS

SPRINGS OIL

2 HOLES 2 HOLES

Holes mm mm

Thickness 2.0mm 2.5mm Precision KIT ALU

DOWNSTOP SHIM INSERT UNDER PISTON

LENGTH mm

UPSTOP SHIM INSERT ABOVE COLLAR

COMP. 0mm 2mm 4mm ALU

BALL JOINT 0mm +2mm +4mm

FRONT ANTI ROLL BAR

THICKNESS /mm

FRONT TIRES

BRAND

COMPOUND

INSERTS

WHEELS

ELECTRONICS

MOTOR SPEEDO

MOTOR TIMING BATTERY

BODY LIGHT

TOTAL WEIGHT /g

COMMENT

