B-MAX4 III

Arn0

SETTING SHEET Ver.04

DRIVER Shin Adachi | **DATE** 01 Feb 2015

CIRCUIT EOS Rd2 Berlin

- ● INDOOR ○ OUTDOOR
- ○ WET ○ DRY ○ DUSTY ● SMOOTH ○ BUMPY ○ OTHER
- ○ LOW TRACTION ● MED TRACTION ○ HIGH TRACTION
- ○ CLAY ○ GRASS ○ BLUE GROOVE ○ ASTROTURF ○ DIRT ● CARPET ○ WOOD

FRONT

0 mm

CAMBER 2.5 °

1.5 mm

1 mm

0 mm

0 mm

0 mm

17 mm

TOE-IN (+) / OUT (−) ____ °

+1 mm +1 mm

FF FR

○ B4-413A8
● B4-413A15

○ 1.0 ○ 1.1
○ 1.2 ○ 1.3
○ 1.4 ○ 1.5
○ 1.6 ● 1.8

○ BALL DIFF
● GEAR DIFF
20k

mm 18.5 mm

○ X SHOCK
SPRING
○ BLACK
● Purple Yatabe Spring

PRELOAD ____

OIL
600

○ #1 ○ #2 ○ #3 ○ #4
● 2x1.6

1 mm x 3

mm x

REAR

mm

2 mm

RF RR

-0.5° +0.5°

2.5 mm

0° 0.5° 1°

S M L

CAMBER 2.5 °

0 mm

17 mm

○ BM-008R
○ B4-BWR

○ 1.0 ○ 1.1
○ 1.2 ○ 1.3
○ 1.4 ○ 1.5
○ 1.6 ● 2.0

○ BALL DIFF
● GEAR DIFF
10k

mm 26.75 mm

○ X SHOCK
SPRING
○ BLACK
○ Orange Yatabe Spring

PRELOAD ____

OIL
450

○ #1 ○ #2 ○ #3 ○ #4
○ 2x1.7

1 mm x 2

mm x

Use YZ-2 shocks front & rear

DRIVE

mm

MOTOR ⇨ Reedy 5.0 ○ Bonded ○ Sintered mm

GEAR ⇨ Spur 81 T / Pinion 18 T : 2.35

BATTERY ⇨ Reedy Shorty

ESC ○ Racing Performer X Series / / /

○ BL-R3 ● SE 140R

Battery placement

FRONT

○ Shorty

TIRE

FRONT

TIRE ⇨ Handout

INSERTS ⇨ Handout

WHEELS ⇨ Handout

REAR

TIRE ⇨ Handout

INSERTS ⇨ Handout

WHEELS ⇨ Handout

OTHER

○ ● ○ ○ ○

COMMENT

Editable by Arn0 at PetitRC.com

All titaminum screw
All titaminum turnbuckle
YZ-2 rear arms
YZ-2 drive shaft (60.5mm)
6.0mm wheel hex hub
1.5mm wheel spacer
Modified front steering hub 2mm back