

MO 2.0

SETTING SHEET Ver.01

CIRCUIT
 INDOOR OUTDOOR
 DIRT ASTROTURF CARPET GLASS WOOD
 WET DRY DUSTY SMOOTH BUMPY
 HARD PACKED CLAY BIUE GROOVE _____
 LOW TRACTION MED TRACTION HIGH TRACTION

DRIVER _____ **DATE** _____

FRONT

◆CAMBER ↔ _____ °
 ◆TOE IN OUT _____ °
 ◆RIDE HEIGHT _____ mm

○Plastic
○Graphite
○Standard ○Graphite

○Dot0(SF)
○Dot1 (MO Series)
○Plastic
○Aluminum

Plastic ○ Aluminum ○
 6° ○
 8° ○
 10° ○
 12.5° ○
 15° ○

○5.0
○ _____

FF ○05 ○1 FR ○05 ○1

SPRING
 Dot _____

OIL
 # _____
 ○ φ1.6×2/2.0
 ○ _____
 _____ mm X
 _____ mm X

REAR

◆CAMBER ↔ _____ °
 ◆RIDE HEIGHT _____ mm

○Plastic
○Aluminum

○5.0
○ _____

Standard ○Graphite

S M L
 ○0.5
 ○1
 ○1.5

RF ○05 ○1 RR ○05 ○1
 ○S4-300RF2 (1W) ○ _____ X _____
 ○ _____ X _____

SPRING
 Dot _____

OIL
 # _____
 ○ φ1.7×2/2.0
 ○ _____
 _____ mm X
 _____ mm X

DRIVE

F/# _____
 ○2 ○4 gear
 R/# _____
 ○2 ○4 gear

CENTER POSITION Forward Back
 ○F2 ○R2
 ○F1 ○R1
 ○F0 ○R0
 ○R-0.5

_____ mm # _____

MOTOR ⇨ _____ Rotor _____ mm
 GEAR ⇨ Spur T / Pinion T : 2.5
 BATTERY ⇨ _____
 ESC ⇨ _____
 SETTING ⇨ _____

○Forward ○Back ○YT-RWS10A X _____
 Brace plate
 Main chassis
 ○M01.0
 ○M02.0
 ○Plastic
 ○Carbon
 Chassis brace
 Side plate

TIRE

FRONT
 TIRE ⇨ _____
 INSERTS ⇨ _____
 WHEELS ⇨ _____

REAR
 TIRE ⇨ _____
 INSERTS ⇨ _____
 WHEELS ⇨ _____

OTHER

○ Z2-DTM31WA (Aero Hi-clearance 7")
 ○ Z2-CAL2WA (LMR27)
 ○ _____

COMMENT

