

SO 2.0

SETTING SHEET Ver.01

CIRCUIT

- INDOOR OUTDOOR
 DIRT ASTROTURF CARPET GLASS WOOD
 WET DRY DUSTY SMOOTH BUMPY
 HARD PACKED CLAY BIUE GROOVE _____
 LOW TRACTION MED TRACTION HIGH TRACTION

DRIVER

DATE

FRONT

Z2-017GA (DTM3.1)
 Z2-017-3A (S01.0/2.0)

Plastic
 Aluminum

Wide Narrow
 Plastic
 Aluminum

Standard (Z2-008F3A)
 Graphite (Z2-008F3GA)

+1 ↑ Plastic
 0 ↑ Aluminum
 Steel

Graphite
 Hard

A/B A/B-
 A/B A/B-
 Wide Narrow

Wide (S02.0)
 Wide
 Narrow

CAMBER ↔ _____ °
 TOE IN OUT _____ °
 RIDE HEIGHT _____ mm

SPRING

Dot _____

OIL

 φ1.6x2/2.0

 _____ mm x _____
 _____ mm x _____

REAR

Plastic
 Aluminum

L5 Standard Graphite
 Plastic
 Z2-415RS2A (Aluminum)

Standard (S01.0/2.0)
 High mount (DTM3.1)

RF 05 01
 RR 05 01

CAMBER ↔ _____ °
 RIDE HEIGHT _____ mm

S M L
 0.5
 1
 1.5

SPRING

Dot _____

OIL

 φ1.7x2/2.0

 _____ mm x _____
 _____ mm x _____

DRIVE

OLD LC
 03
 02
 01
 00

4-gear
 2-gear
 # _____

MOTOR _____ Rotor _____ mm
 GEAR Spur T / Pinion T : 2.6
 BATTERY _____
 ESC _____
 SETTING _____

Main chassis

Steel
 Aluminum

OS02.0
 OS01.0
 ODTM3.1
 OAL3.1

YT-RWS10A x _____
 YT-RW25A x _____

Steel
 Aluminum
 Plastic
 Carbon

TIRE

FRONT
 TIRE _____
 INSERTS _____
 WHEELS _____

REAR

TIRE _____
 INSERTS _____
 WHEELS _____

OTHER

Z2-DTM31 WA (Aero Hi-clearance 7')
 Z2-CAL2WA (LMR27)

COMMENT