

SO 2.0

SETTING SHEET Ver.01

CIRCUIT

- INDOOR OUTDOOR
 DIRT ASTROTURF CARPET GLASS WOOD
 WET DRY DUSTY SMOOTH BUMPY
 HARD PACKED CLAY BIUE GROOVE _____
 LOW TRACTION MED TRACTION HIGH TRACTION

DRIVER

DATE

FRONT

Z2-017GA (DTM3.1)
 Z2-017-3A (S01.0/2.0)

Plastic
 Aluminum

Wide Narrow
 Plastic
 Aluminum

Standard (Z2-008F3A)
 Graphite (Z2-008F3GA)

+1 ↑ Plastic
 0 ↑ Aluminum
 Steel

Graphite
 Hard

4.5
 5.0

0°
 2.5°
 5°

A/B
 A/B
 A/B
 A/B
 Wide
 Narrow

Wide (S02.0)
 Wide
 Narrow

CAMBER ↔ _____ °
 TOE IN OUT _____ °
 RIDE HEIGHT _____ mm

SPRING
 Dot _____

OIL
 # _____
 φ1.6x2/2.0

 _____ mm x _____
 _____ mm x _____

REAR

Plastic
 Aluminum

L5
 S3
 Standard
 Graphite

Plastic
 Z2-415RS2A (Aluminum)

4.3
 5.0
 6.0

0.5
 1
 1.5

S
 M
 L

Standard (S01.0/2.0)
 High mount (DTM3.1)

RF 0.05 0.1
 RR 0.05 0.1

CAMBER ↔ _____ °
 RIDE HEIGHT _____ mm

SPRING
 Dot _____

OIL
 # _____
 φ1.7x2/2.0

 _____ mm x _____
 _____ mm x _____

DRIVE

OLD
 LC

03
 02
 01
 00

4-gear
 2-gear

MOTOR ⇨ _____ Rotor _____ mm
 GEAR ⇨ Spur T / Pinion T : 2.6
 BATTERY ⇨ _____
 ESC ⇨ _____
 SETTING ⇨ _____

Main chassis
 S02.0
 S01.0
 DTM3.1
 CAL3.1

Steel
 Aluminum

YT-RWS10A x _____
 YT-RW25A x _____

Steel
 Aluminum
 Plastic
 Carbon

TIRE

FRONT
 TIRE ⇨ _____
 INSERTS ⇨ _____
 WHEELS ⇨ _____

REAR
 TIRE ⇨ _____
 INSERTS ⇨ _____
 WHEELS ⇨ _____

OTHER

Z2-DTM31 WA (Aero Hi-clearance 7')
 Z2-CAL2WA (LMR27)

COMMENT